



HygroMaster 2

Thermo-Hygrometer with Psychrometric Calculation



The all new Protimeter HygroMaster 2 is the latest in hand-held hygrometry, featuring a simple to use interface and multi-function capability.

Features

- Infrared non-contact surface temperature
- Psychrometric Calculations
- Data logging
- Simple to use interface with color display

Benefits

- Fast temperature and humidity response
- Replaceable humidity and temperature sensor
- Highly accurate

Applications

- Flood damage restoration
- Building survey
- Concrete moisture
- HVAC test and measurement
- Commercial coatings

Amphenol
Advanced Sensors



99 Washington Street
Melrose, MA 02176
Phone 781-665-1400
Toll Free 1-800-517-8431

 Visit us at www.TestEquipmentDepot.com

HygroMaster 2 Options

Protimeter	HygroMaster 2	Short QuikStick	HygroStick	Cable	Carry Case	Surface Temp Sensor	Flooring Kit	Humidity Extension Lead	Humidity Probe (30cm)
	POL7750	POL8751	POL4750	BLD7759	441-1023	BLD5808	BLD7750-CKIT	BLD5802	BLD8755
BLD7750	S	O	S	S	S	O	O	O	O
BLD7751	S	S	O	S	S	O	O	O	O

S = Standard Supply O = Optional

Note: BLD7751 with short QuikStick is recommended for general measurement and BLD7750 with Hygrostick is recommended for high RH harsh environment applications such as ERH concrete floor measurement.

HygroMaster 2 Specifications

Gross Weight

8 oz (277 gms)

Dimensions (LxWxH)

7 in x 3.2 in x 1.5 in (178 mm x 81 mm x 38 mm)

Display

2" TFT color display, 176 x 220, 256K color

Batteries (Included)

9V Alkaline

Warranty

24 months on mechanical or manufacturing defects.
Does not include wearing part or accessories.

Plug in Temperature Probe Surface Temperature Probe - BLD5808

Range 32°F to 158°F (0°C to 70°C)
Accuracy at 77°F (25°C) +/- 1.3°F (0.7°C)

Infrared Surface Temperature Range

IR Based – With 12:1 (D:S) Ratio
Range -4°F to 176°F (-20°C to 80°C)
Accuracy ±3.6°F (±2°C)



HygroStick Data (Nominal)

30% to 40% RH (±3% RH) at 68°F (20°C).
41% to 98% RH (±2%) at 68°F (20°C).
Range 32°F to 122°F (0°C to 50°C) ±0.6°F (±0.3°C)

QuikStick and QuikStick ST Data (Nominal)

0% to 10% RH, ±3% RH at 68°F (20°C),
10% to 90% RH, ±2% RH at 68°F (20°C),
90% to 100% RH, ±3% RH at 68°F (20°C),
Range 32°F to 122°F (0°C to 50°C) ±0.6°F (±0.3°C)
Nominal response 30% to 90% and back to 30% RH in 45 seconds @ 68°F (20°C)

Data Storage

Store up to 8,000 results with date and time stamp from all instrument functions with the push of a button. Store 6100 results with automatic logging.



99 Washington Street
Melrose, MA 02176
Phone 781-665-1400
Toll Free 1-800-517-8431

Visit us at www.TestEquipmentDepot.com

Amphenol

Advanced Sensors