

# Ultra-Broadband LogPer Antennas up to 35GHz HyperLOG<sup>®</sup> 30250 & 30350

Ultimate Functionality, Ultra Wideband, Compact & Directional

### Highlights:

- Only a single broadband antenna for the complete frequency range from 380MHz to 35GHz
- Optimal for usage with spectrum analysers for EMC measurement
- Complete ISO calibration certificate (option)
- Top-quality high-tech TEFLON antenna
- support
  Freely alignable polarisation
- Made in Germany

### Calibration & standards:

- The log-periodic precompliance test antenna of the HyperLOG<sup>®</sup> 30xxx series are suitable for interference field strength measurement. The specialized broadband characteristics allow measurements to be taken in the complete specified frequency range without switching.
- These antennas are suitable for measurement according to the following standards and procedures: CISPR, VDE, MIL, VG, EN 55011, EN 55013, EN 55015, EN 55022, MIL-Std-461.

### Included with delivery:

- HyperLOG<sup>®</sup> 30xxx-Antenna
- Typical calibration data with up to 693 calibration points (50MHz steps)
- Aluminum design carrycase with custom padding
- Sturdy, detachable pistol grip with "miniature tripod" mode
- Special Aaronia SMA toolset with overtorque protection

Made in Germany

### HyperLOG® 30250

- Design: Logarithmic-periodic
- Frequency range: 380MHz-25GHz
- Max. transmission power: 100W CW (400 MHz)
- Nominal impedance: 50 Ohms
- VSWR (typ.): <1:2,5</li>
- Gain (typ.): 5dBi
- Calibration points: 493 (50MHz-steps)
- RF connection: SMA (female) or N via Adapter
- Dimensions (L/W/D): (590x360x30) mm
- Weight: 1000gr


### HyperLOG<sup>®</sup> 30350

- Design: Logarithmic-periodic
- Frequency range: 380MHz-35GHz
- Max. transmission power: 100W CW (400 MHz)
- Nominal impedance: 50 Ohms
- VSWR (typ.): <1:2,5</li>
- Gain (typ.): 5dBi
- Calibration points: 693 (50MHz-steps)
- RF connection: SMA (female) or N via Adapter
- Dimensions (L/W/D): (590x360x30) mm
- Weight: 1000gr






#### Horizontal Pattern HyperLOG 30xx Serie






Antenna Factor HyperLOG 30350



#### Vertikal Pattern HyperLOG 30xx Serie



# **Description**



HyperLOG 30xxx antenna with optional aluminum tripod


The HyperLOG® antennas come standard with a specially constructed, high tech radom housing. This housing has been constructed after intense research with the most modern computer technology in such a way that its shape, material and special coating have virtually no influence on measurements, not even in case of dew or other kinds of humidity collecting on the surface. Another important factor for Aaronia was the development of a radom with the lowest possible damping factor achievable. This turned out to be quite an adventure for our development team, particularly in the high GHz ranges. Fortunately, this adventure has been mastered resulting in a beautiful, elegant design, to the complete satisfaction of the development team. Our first test measurements even by far surpassed our guidelines!

The resulting antenna had the best possible protection against mechanical stress and environmental influence without sacrificing any of its performance.



Lot of space for optionally accessories: The HyperLOG<sup>®</sup> transportcase With their log-periodic measurement antennas from the HyperLOG<sup>®</sup> 30xxx series, Aaronia finally offers a very cost-effective alternative, which at the same time meets the highest expectations. In conjunction with the HyperLOG<sup>®</sup> antennas, every regular spectrum analyser becomes a fully professional directional RF measurement device within a few moments. Thus, a perfect "dream team" for EMC measurement in the laboratory or for outdoor use is at your disposal.

The TEFLON LogPer antennas of the HyperLOG<sup>®</sup> 30xxx series are identical to those of the 60xxx series, but have an enhanced frequency range down to 380MHz, particularly for coverage of the important TETRA band. After a huge amount of complex development, a whole series of truely high-tech antennas has evolved, with an exceptional mix of performance, functionality and design in this price category.



Gold coated, protected TEFLON precision antenna

Included with delivery: A sturdy aluminum design carrycase with custom padding for the antenna, cables and accessories. Furthermore, every antenna of the HyperLOG<sup>®</sup> 30xxx series includes a detachable multi-functional pistol grip with "miniature-tripod" mode and an appropriate SMA toolset.

# Accessories

#### **Aluminum tripod**

Height adjustable, high stability. STRONGLY recommended for use with HyperLOG 40xx and 30xxx antennas! Max. height: 105cm.

Order/Art.-No.: 281

#### 1m / 5m / 10m SMA-Cable

High quality special SMA cable for connecting any HyperLOG<sup>®</sup>-Antenna or BicoLOG<sup>®</sup>-Antenna with various test equipment like our RF Spectrum-Analyzer. You can choose between 3 different cables:

1m standard SMA cable (RG316U) 5m LowLoss SMA cable (especially low damping) 10m LowLoss SMA cable (especially low damping)

All versions: SMA plug (male) / SMA plug (male)

Order/Art.-No.: 771X (1m Cable), 772X (5m Cable), 773X (10m Cable)



This special high quality adapter allows operation of all HyperLOG<sup>®</sup>-Antenna with any standard spectrum-analyzer with N connector. Also this adapter is needed to connect BicoLOG<sup>®</sup> antennas to a Spectran Spectrum Analyzer.

Especially massive, chrome-plated design. This adapter is usable for very high frequencies up to at least 18GHz. Physical dimensions are just 30x20mm. Nominal impedance 50 Ohms. Layout: SMA socket (female) / N plug (male).

Order/Art.-No.: 770

### Heavy multifunctional Pistol Grip (strongly recommended!)

Highly recommend for the usage of HyperLOG antennas. Quick and easy change of antenna polarization, perfect antenna handling.

Order/Art.-No.: 282







# References

## **Cross-Section of Aaronia Clients**

### Government, Military, Aeronautic, Astronautic

- NATO, Belgium
- Department of Defense, USA
- ٠ Department of Defense, Australia
- Airbus, Germany
- Boeina, USA Bundeswehr, Germany
- NASA, USA
- Lockheed Martin, USA Lufthansa, Germany
- DLR,Germany
- Eurocontrol, Belgium
- EADS, Germany
- DEA, USA
- FBI, USA
- BKA, Germany
- Federal Police, Germany
- Ministry of Defense, Netherlands

### Research/Development, Science and Universities

- MIT Physics Department, USA
- California State University, USA
- Indonesien Institute of Sience, Indonesia
- Los Alamos National Labratory, USA
- · University of Bahrain, Bahrain
- University of Florida, USA
- University of Victoria, Canada
- University of Newcastle, United Kingdom
- University of Durham, United Kingdom
- University Strasbourg, France
- University of Sydney, Australia
- University of Athen, Greece ٠
- University of Munich, Germany ٠
- Technical University of Hamburg, Germany
- Max-Planck Institute for Radio Astronomy, Germany ٠
- Max-Planck Institute for Quantum Optics, Germany
- Max-Planck-Institute for Nuclear Physics, Germany ٠
- Max-Planck-Institute for Iron Research, Germany
- Research Centre Karlsruhe, Germany

### Industry

- APPLE, USA
- IBM, Switzerland
- Intel, Germany
- Shell Oil Company, USA
- ATI, USA
- Microsoft, USA
- Motorola, Brazil
- Audi, Germany
- BMW, Germany
- Daimler, Germany
- Volkswagen, Germany
- BASF, Germany
- Siemens AG, Germany
- Rohde & Schwarz, Germany
- Infineon, Austria
- Philips, Germany
- ThyssenKrupp, Germany
- EnBW, Germany
- RTL Television, Germany
- Pro Sieben SAT 1, Germany
- Channel 6, United Kingdom
- CNN, USA
- Duracell, USA
- German Telekom, Germany
- Bank of Canada, Canada
- NBC News, USA
- Sony, Germany
- Anritsu, Germany
- Hewlett Packard, Germany
- Robert Bosch, Germany
- Mercedes Benz, Austria
- Osram, Germany
- DEKRA, Germany
- AMD, Germany
- Keysight, China
- Infineon Technologies, Germany
- Philips Semiconductors, Germany
- Hyundai Europe, Germany
- JDSU, Korea
- Wilkinson Sword, Germany
- IBM Deutschland, Germany
- Nokia-Siemens Networks, Germany

Test Equipment Depot - 800.517.8431 - 5 Commonwealth Ave, MA 01801 - TestEquipmentDepot.com