

# RIDGID®

## K-4310 FXP™ Drum Machine

Test Equipment  
Depot  
1-800-517-8431

5 Commonwealth Ave  
Woburn, MA 01801  
Phone 781-665-1400 Toll  
Free 1-800-517-8431

Visit us at [www.TestEquipmentDepot.com](http://www.TestEquipmentDepot.com)



### Powers Through the Toughest Jobs

**FXP**  
TECHNOLOGY PLATFORM

The RIDGID® K-4310 FXP™ Drum Machine is RIDGID's most powerful drum machine, delivering best-in-class performance. Powered by the FXP Technology Platform, this machine lets you switch between the battery and power adapter for convenience and all-day runtime. The Cable Counter gives real-time feedback measuring cable distance in 3" to 10" lines on residential and commercial jobs, making this a valuable addition to your truck.

- **Performance:** RIDGID's most powerful drum machine features a Brushless DC Motor and spins up to 230 RPM
- **Power:** FXP Battery and Power Adapter provide continuous uptime and powerful performance
- **Real-Time Machine Feedback:** Cable Counter measures cable distance in drain line
- **Efficiency:** Quick-change drum allows for toolless setup and easy transport
- **Speed:** AUTOFEED® Technology advances and retrieves cable up to 28' (8.5 m) per minute with zero tools required for setup
- **Connected:** Create shareable job insights, maintenance reminders, and tool history with the RIDGID® Link app



## SPECIFICATIONS

- Capacity ..... 3" – 6" (5/8" Cable)  
4" – 10" (3/4" Cable)
- Drum Capacity, 5/8" Drum ..... 100' (30.5m) of 5/8" (16mm) Diameter Cable
- Drum Capacity, 3/4" Drum ..... 125' (38.1m) of 5/8" (16mm) Diameter Cable,  
100' (30.5m) of 11/16" (17.5mm) Diameter Cable  
100' (30.5m) of 3/4" (20mm) Diameter Cable
- Maximum Reach ..... 250' (76m)
- Power Source ..... RIDGID® FXP Battery Pack or  
FXP Power Adapter (*in development*)
- Motor Type ..... Brushless DC Motor
- Watts ..... 810 W
- Amps ..... 15 A
- Voltage ..... 54V DC Nominal
- No Load Output Speed ..... 230 RPM
- Weight (No Cable) ..... 123 lbs. (55.8 kg)
- Weight (w/100' of 5/8" Cable) ... 193 lbs. (87.5 kg)
- Weight (w/100' of 3/4" Cable).... 237 lbs. (107.5 kg)
- Dimensions (Handle Down) ..... 37" x 22" x 35" (940mm x 559mm x 889mm)
- Controls ..... Main ON-OFF Switch, FOR/OFF/REV Switch, Pneumatic Foot Switch,  
AUTOFEED® Cable Feed Unit Handle



\* Drum includes 5/8" or 3/4" Pigtail. Cable sold separately.



## ORDER INFORMATION

CATALOG NO.	MODEL NO.	DESCRIPTION	WEIGHT (lb.) (kg)
73048	K-4310 FXP	K-4310 FXP 3/4" Drum Machine (3/4" Pigtail Only) with FXP Battery - 8.0 Ah (Qty-2) & Charger	145.8 66.1
73073	K-4310 FXP	K-4310 FXP 5/8" Drum Machine (5/8" Pigtail Only) with FXP Battery - 8.0 Ah (Qty-2) & Charger	138.9 63.0

## ACCESSORIES

CATALOG NO.	MODEL NO.	DESCRIPTION
70788	RB-FXP40	FXP Battery – 4.0 Ah
70793	RB-FXP80	FXP Battery – 8.0 Ah
70798	RBC-FXP	FXP Battery Charger
73093	—	K-4310 FXP 3/4" Drum Only
73098	—	K-4310 FXP 5/8" Drum Only
73083	—	AUTOFEED® Assembly
41697	C-100	3/4" x 100' Inner Core Cable
43647	C-24	5/8" x 100' Inner Core Cable

Note: Additional Drum Machine Cables & Tools Ordering Information can be found on RIDGID.com.



FXP Power Adapter  
(In Development)



All sales subject to Ridge Tool Company Terms and Conditions of Sales. Catalog Sheet No. R-23-Q (0423) Effective Date: February 25, 2023  
©2023 Ridge Tool Company

Test Equipment Depot - 800.517.8431 - 5 Commonwealth Ave, MA 01801 - TestEquipmentDepot.com