

ZOOM 2 / Laser OWL Test Kit

SKU: KIT-Z2-L2st

Singlemode Fiber Test Kit

Overview

The **ZOOM 2 / Laser OWL Test Kit** is ideal for LAN managers and installers who need to do simple attenuation tests on their singlemode networks.

The **ZOOM 2 (Zeroed Output Optical Meter)** is an economical fiber optic power meter. It provides accurate testing of singlemode fiber cables. The 4-digit 7-segment LCD displays power readings with a resolution of 0.01dB. On-screen indicators display measurement units (dBm, dB, uW), as well as battery life. The ZOOM 2 comes configured with a 2.5mm universal connector for connection to ST or SC connectors, as well as any other fiber connector with a 2.5mm ferrule, and includes a 1.25mm adapter cap for LC connections.

The **Laser OWL** is a 1310/1550nm NIST traceable singlemode light source. Its dual wavelength outputs are temperature-stabilized for accurate measurements. The Laser OWL comes configured with ST connectors.

Kit Contents

Power Meter: ZOOM 2 (ZO-2)

Light Source: Laser OWL (LO2st)

Accessories: Product manuals
Battery chargers
NIST certificate
Carrying case
Protective rubber boots

Features

Economical option for quick attenuation and loss testing singlemode networks

Easy-to-read 4-digit 7-segment backlit LCD display

Re-chargeable Lithium Polymer battery

Store reference values for calibrated wavelengths

Intuitive 2-button interface on both units

On-screen wavelength, measurement units, and low battery indicator

NIST traceable


Light source comes configured with ST connector.

Other source connectors may be available.



ASSEMBLED IN USA

N.I.S.T. Traceable



ZOOM 2 / Laser OWL Test Kit

SKU: KIT-Z2-L2sc

Singlemode Fiber Test Kit

ZOOM 2 OPTICAL POWER METER (ZO-2)

KEY SPECIFICATIONS	
Detector Type	InGaAs
Calibrated Wavelengths ¹	850, 1300, 1310, 1490, 1550
Measurement Range	+5 to -60 dBm
Accuracy	±0.20 dB
Display Resolution	0.01 dB
Battery Life	Up to 1000 hours (Re-chargeable Lithium Polymer)
Connector Type	2.5mm/1.25mm universal
Measurement Units	dBm, dB, mW, μW
Display Type	Backlit LCD
Auto-shutdown	Yes
Operating Temperature	-10 to 55° C
Storage Temperature	-30 to 70° C
Dimensions	2.75 x 4.94 x 1.28 inches (69.85 x 125.48 x 32.51 mm)
Weight	10 oz. (284g)

1: Bold wavelengths are NIST Traceable

Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.

LASER OWL SINGLEMODE LASER SOURCE (LO2st)

KEY SPECIFICATIONS	
Fiber Type	Singlemode
Launch Method	FP Laser
Center Wavelength	1310nm ± 20nm; 1550nm ± 30nm
Spectral Width	1310nm: 2nm; 1550nm: 2nm
Output Power	-10 dBm
Initial Accuracy	0.1 dB
Battery Life	Up to 120 hours (Re-chargeable Lithium Polymer)
Operating Temperature	0 to 55° C
Storage Temperature	0 to 70° C
Dimensions	2.75 x 4.94 x 1.28 inches (69.85 x 125.48 x 32.51 mm)
Weight	10 oz. (284g)

Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.

Other connector styles may be available. Call for more information.

