## **R** Ralston Instruments



Test Equipment 99 Washington Street Depot Melrose, MA 02176 Phone 781-665-1400 Toll Free 1-800-517-8431

Visit us at www.TestEquipmentDepot.com

### Part No.

LC10-GD2M

LC10 pressure gauge, 15 psi / 1 bar / 100 kPa, 1/4" Male NPT bottom connection

The LC10 is a robust device that measures and displays pressure readings on a large, backlighted screen. The LC10 has the ability to show High and Low pressure values on-screen, change between 15 different engineering units or add custom engineering units. The included PC FieldLab Desktop software can be used for calibration, testing and live viewing of pressure.



LC10-GD2M

#### 2 **Battery Count** Battery Life 1500 Hours **Battery Type** AA Alkaline (LR6) **Burst Pressure** 60 PSI / 5 bar / 500 kPa Certifications Certified to CSA Standard C22.2 No. 61010-1, Conforms to UL / IEC / EN / AS Standard No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU Country of origin USA **Electrical Rating** 50 mA @ 5 VDC atm, bar, cmH2O @4°C, inH2O @39°C, kPa, mbar, psi, inHg @39°F, kgf / cm^2, mmHg @0°C, Torr, **Engineering Units** mmH2O @4°C, ftH2O @39°F, cmHg @ 0°C, oz / sqin **Ingress Protection** IP67 (1 meter water submersion for 30 minutes) LCD Display 2.4 in / 61 mm segmented LCD Display Materials ABS / Polycarbonate Blend, Powder Coated Aluminum Max Pressure 15 PSI / 2 bar / 200 kPa 165 °F / 75 °C Max Storage Temperature 120 °F / 50 °C Max Temperature Measurement Type **Gauge Pressure** Media Compatibility Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Mineral Oil, Natural Gas, Petroleum Based Oil, Skydrol, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil, Water -40 °F / -40 °C Min Storage Temperature Min Temperature -4 °F / -20 °C

### Specs/Attributes

# **R** Ralston Instruments

## Specs/Attributes

Operating Altitude (max)	10,000 ft (3050 m)
Pressure Measurement Uncertainty	+/- 0.25% of Full Scale (ASME Grade 3A/ISO Class 0.25)
Process Connection	1/4" Male NPT
Protection Class	Pollution Degree 2 (UL / IEC 61010-1)
Relative Humidity	0% to 90% (-10 to 35°C) , 0% to 70% (35 to 50°C)
USB Connection	USB (Micro B)
Wetted Materials	316 Stainless Steel
Wrench Size	7/8 ln 23 mm
Weight	12.6 oz / 355 grams
Dimensions	H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 4.1 in (10.41 cm)



Depot Melrose, MA 02176 Phone 781-665-1400 Toll Free 1-800-517-8431

Visit us at www.TestEquipmentDepot.com