

Part No.

# LC10-GT2M

*LC10 pressure gauge, 5000 psi / 350 bar / 35 MPa, 1/4" Male NPT bottom connection*

The LC10 is a robust device that measures and displays pressure readings on a large, backlit screen. The LC10 has the ability to show High and Low pressure values on-screen, change between 15 different engineering units or add custom engineering units. The included PC FieldLab Desktop software can be used for calibration, testing and live viewing of pressure.

Visit us at [www.TestEquipmentDepot.com](http://www.TestEquipmentDepot.com)



LC10-GT2M

## Specs/Attributes

Battery Count	2
Battery Life	1500 Hours
Battery Type	AA Alkaline (LR6)
Burst Pressure	20000 PSI / 1380 bar / 140 MPa
Certifications	Certified to CSA Standard C22.2 No. 61010-1, Conforms to UL / IEC / EN / AS Standard No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU
Country of origin	USA
Electrical Rating	50 mA @ 5 VDC
Engineering Units	atm, bar, kPa, MPa, psi, inHg @39°F, kgf / cm <sup>2</sup> , ftH <sub>2</sub> O @39°F, cmHg @ 0°C, oz / sqin
Ingress Protection	IP67 (1 meter water submersion for 30 minutes)
LCD Display	2.4 in / 61 mm segmented LCD Display
Materials	ABS / Polycarbonate Blend, Powder Coated Aluminum
Max Pressure	5000 PSI / 345 bar / 35 MPa
Max Storage Temperature	165 °F / 75 °C
Max Temperature	120 °F / 50 °C
Measurement Type	Gauge Pressure
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Storage Temperature	-40 °F / -40 °C
Min Temperature	-4 °F / -20 °C
Operating Altitude (max)	10,000 ft (3050 m)

## Specs/Attributes

Pressure Measurement Uncertainty	+/- 0.25% of Full Scale (ASME Grade 3A/ISO Class 0.25)
Process Connection	1/4" Male NPT
Protection Class	Pollution Degree 2 (UL / IEC 61010-1)
Relative Humidity	0% to 90% (-10 to 35 °C) , 0% to 70% (35 to 50 °C)
USB Connection	USB (Micro B)
Wetted Materials	316 Stainless Steel
Wrench Size	23 mm 7/8 In
Weight	12.6 oz / 355 grams
Dimensions	H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 4.1 in (10.41 cm)

