



**Mastercool**<sup>®</sup> Inc.  
"World Class Quality"

## SPARK FREE TWIN TURBO COMBUSTIBLE GAS RECOVERY MACHINE



### SPECIFICATIONS:

- 1/2 hp oil less compressor
- Operating temperature: 32 to 122°F
- Weight: 28.3 lbs
- Dimensions: 18" (l) x 10" (w) x 14" (h)
- Case material is HDPE (high density polyethylene)
- Compatible refrigerants: all CFC, HCFC, and HFC's
- Compatible with combustible gases

*Spark Free*  
**TWINTURBO**  
REFRIGERANT RECOVERY MACHINE

- **COMPATIBLE WITH ALL CFC, HCFC AND HFC'S**
- 1/4" flare fittings

**69395:** 115 V / 60 Hz

**69395-220:** 220 V – 50/60 Hz

**APPROVED FOR ALL  
AIR CONDITIONING REFRIGERANTS  
INCLUDING A2L AND A3  
FLAMMABLE REFRIGERANTS**

### FEATURES & BENEFITS:

- Largest volume recovery rate in market
- Sealed crank case eliminated refrigerant loss during the recovery process
- Revolutionary double piston oil-less compressor provides fast recovery times
- Large, easy to read 2 1/2" gauges
- Purge valve ensures 100% refrigerant removal from the condenser and the recovery machine
- Large fan and condenser keeps the unit running cooler and speeds up the recovery process
- Safety high pressure switch
- Simple internal structure for field service
- For use with all refrigerants including R410A
- Injection molded high density polyethylene case for maximum durability
- Front cover has bumper guards built in to reduce damage to the control knobs