

# RIDGID®

## micro IR-200 Infrared Thermometer



The RIDGID® micro IR-200 Non-Contact Infrared Thermometer provides simple, quick and accurate surface temperature readings at the push of a button. Simply squeeze the trigger and point the ultra-sharp dual class II lasers at the surface being measured.

- Ultra Sharp Dual Class II Lasers easily identify the surface area being measured.
- 30 To 1 Distance To Spot Ratio allows you to take more accurate measurements from a farther distance.
- Adjustable Emissivity to accurately measure the temperature of virtually any surface.
- Audible and Visual High and Low Alarms quickly alert you to temperatures outside of the ranges that you set.
- Bright Backlit Display which can be toggled on in poorly lit areas.
- Tripod Mount Capable for repeatable, precise temperature measurements.



## SPECIFICATIONS

- Temperature Range.....-58° to 2192°F (-50° to 1200°C)
- Measurement Accuracy .....-58°F to 68°F (-50°C to 20°C) ±4.5°F (2.5°C)  
68°F ~2192°F (20°C ~1200°C)  
±1.0% or ±1.8°F (1.0°C)
- Distance To Spot Ratio .....30 to 1
- Response Time .....<150ms
- Emissivity .....Adjustable, 0.10 - 1.00
- Temperature Display.....Current Temperature, MAX Temperature
- Measurement Units.....Fahrenheit, Celsius
- Power Source .....Battery (1 x “9V”) Included



## ORDER INFORMATION

CATALOG NO.	DESCRIPTION	WEIGHT	
		(lb.)	(kg.)
36798	micro IR-200 Non-Contact Infrared Thermometer	.5	0.2



SR-20  
Line Locator

micro LM-100  
Laser Distance Meter



micro CD-100  
Combustible Gas Detector



micro CA-100  
Inspection Camera



ST-510 Transmitter



SeeSnake® microReel™  
Inspection System