

Multimeters Accessories



Model PR-28A
40kV High Voltage DMM Probe

If the voltages you need to measure are above the specifications of general purpose probes, B+K Precision has a higher voltage probe for you.

Features		model	
		PR-28A	
Attenuation	x1000	Impedance	1000MΩ
Voltage (AC)	20kV	Accuracy (AC & DC)	± 3%
Voltage (DC)	40kV	Cable Length	48" (1.2m)
Bandwidth	60Hz		



Model TL-50
Maxi-Pro DMM Kit

Complete accessory kit for all your testing needs. Includes soft, flexible silicone lead wire for easy movement and Tri-Fold Velcro Pouch for convenient storage.

- All components compliant to IEC61010-031
- Silicone Lead Wire length 60" (1.5m)
- Tri-fold Velcro Pouch

Features		model		
		TL-50		
4mm Straight to Right-Angle Silicone Leads, 1.5m		1000V	CATIII	12A
Probe Bodies w/2mm Tip		1000V	CATIII	36A
Pincer Style Clips		1000V	CATIII	6A
Alligator Clips		300V	CATI	3A
Spade Lug Adapters	42V (1000V)			36A
Banana Plug Adapters	42V (1000V)			36A
Fully Insulated Alligator Clips		1000V	CATIII	20A



PR-650A
Model PR-650A
RF DMM Probe

All purpose RF demodulator probe, usable with most DMMs. Allows a DMM to measure sine wave AC signals: $I_{Veff} = 1VDC$. Features light weight design.

Specifications		model	
		PR-650A	
Bandwidth		100kHz to 650MHz	
Accuracy		± 1dB (100kHz-300MHz) ± 3dB (300MHz-650MHz)	
Input Voltage		100V	
HF Voltage		35Veff	
Actuating Voltage		350mV	
DMM Input Impedance		10MΩ	
Input Capacitance		8pF	
Cable Length		48" (1.2m)	



TL-130A
Model TL-130A
General Purpose DMM Kit

If you need only one basic accessory kit for your meter, this is the one. Attach probes or clips to the sheath plug to complete your test. Soft, flexible silicone leads make for movement easy. Kit is voltage and current rated for either electronic or electrical applications.

- All components compliant to IEC61010-031
- Silicone Lead Wire length 60" (1.5m)
- Tri-fold Velcro Pouch

Features		model		
		TL-130A		
4mm Straight to Right-Angle Silicone Leads, 1.5m		1000V	CATIII	12A
Probe Bodies w/2mm Tip		1000V	CATIII	36A
Alligator Style Clips		1000V	CATIII	20A
Alligator Clips		300V	CATI	3A



TL-10
Model TL-10
SMD Probe Kit

Extended, slim-line probe body for easy reach. Use with small SMD components or general purpose test points. Includes soft, flexible silicone lead wires for easy movement and clear, PVC Pouch for convenient storage.

- All components compliant to IEC61010-031
- Silicone Lead Wire length 60" (1.5m)
- Clear PVC Pouch

Features		model		
		TL-10		
4mm Straight to Right-Angle Silicone Leads, 1.5m		1000V	CATIII	12A
Extended Tip Probe Bodies		1000V	CATIII	20A



CP-3
Model CP-3
DC/AC Current Clamp

- Converts any DMM to a current clamp
- Measures current without disconnecting circuit under test
- Measures to 400A DC or AC
- Outputs 1 mV per Amp, operates on 2V range of any DMM

Specifications		model	
		CP-3	
(Accuracy specified at 18° to 28°C)			
Current Range		2A to 400A, DC or AC	
Frequency Response (AC)		50 Hz - 400 Hz	
Accuracy		±(2% reading + 2A)	
Input Resistance		10kΩ min.	
Maximum Conductor Size		1.1"(30mm)	
Power Requirement		9V battery, NEDA 1604	
Battery Life		100 hr typical	
Operating Temperature		0° to 40°C, <70% RH	
Storage Temperature		-20° to +70°C, <80% RH	

Test Accessory Pairs

(Supplied as Black & Red Pairs)

AD-101

Banana Plug Adapter Set

- 42V (1000V) 36A Rating
- w/trained user



AD-101

CC-104

Silicone Lead Set

- Highly Flexible Silicone Jacket
- 4mm Sheathed Straight to Right-Angle Plugs
- 60" (1.5m) length
- IEC61010 1000V CATIII 12A Rating



CC-104

TIP-102

Insulated Alligator Clip Set

- IEC61010 1000V CATIII 20A Rating



TIP-102

TIP-104

Insulated Space Lug Set

- 42V (1000V) 36A Rating
- w/trained user



TIP-104

TIP-110

Very Fine Tip Probe Set

- Extended length w/SS tip
- IEC61010 1000V CATIII 20A Rating



TIP-110

TIP-125A

Alligator Style Clip Set

- Rigid clip body
- IEC61010 1000V CATIII 20A Rating



TIP-125A

TIP-127

Flexible Pincer Clip Set

- Flexible shaft
- IEC61010 1000V CATIII 6A Rating



TIP-127

TIP-129

Standard Alligator Clip Set

- IEC61010 300V CATI 3A Rating



TIP-129

TIP-130

Probe Body Set

- 2mm Probe Tip
- IEC61010 1000V CATIII 36A Rating



TIP-130

TL-140

5-Way Test Clip Set

- 5-Way Communication Clip
- 60" (1.5m) Silicone Leads



TL-140

Multimeters Accessories

Replacement Test Leads

Model TL-2A

Deluxe Test Lead Sets

- IEC61010 1000V CATIII Rating
- Silicone Lead Wire length 60" (1.5m)
- Black Alligator Clip included
- Threaded tips fits TL-3
- Accessory kit items



TL-2A

Model TL-3

Probe Accessory Kit

- Threaded accessories to fit TL-2A probes – Black and Red pairs (except for alligator clip)
- Alligator clip, Red only
- Spring hook clips
- 4" Sharp extension tips to reach tight test points
- No. 10 Spade lugs



TL-3

Model TL-100B

UL Listed Probes w/PVC wire

- IEC61010 1000V CATIII Rating
- UL Listed
- Highly flexible PVC lead wire, 48" (1.2m)
- Black and Red Alligator clips



TL-100B

Model TL-1

Model TL-4

Economical replacement test leads. TL-1 has safety shrouded banana plugs. TL-4 has un-shrouded banana plugs.

- 1500V 3A ratings
- PVC lead wire, 40" (1.0m)
- Black and Red Alligator clips



TL-1

TL-4

TL-8

Surface Mount Tweezers

- Two conductor leads
- 400V rms, 1A



TL-8