

Part No.

# NPAK-TRSO-2MSO-2FSA

*Liquid trap with NPT ports - (1) 1/4" female NPT top connection, (1) 1/4" male NPT bottom connection*

Eliminates unwanted fluid or moisture that can contaminate any gas system.



NPAK-TRSO-2MSO-2FSA

## Included Items

- Top Connection - 1/4" Female NPT outlet port, S.S. (QTHA-3S2F-SS)
- Bottom Connection - Female Quick-test outlet port with drain tube (for NPAK-TRSO), S.S. (QTHA-3SSA-LD)
- Fluid Trap - Fluid and Moisture Trap (TRAP)

## Specs/Attributes

Country of origin	USA
Max Pressure	3000 PSI / 200 bar / 20 MPa
Max Vacuum	23 InHg / 77.9 kPa
Materials	Anodized Aluminum, Stainless Steel

## Specs/Attributes

Seal Materials	Buna-N, Teflon
Min Operating Temperature	0 °F / -18 °C
Max Operating Temperature	130 °F / 54 °C
Weight	1.30 lbs / 590 grams
Dimensions	H: 5.5 in (13.97 cm) x W: 2 in (5.08 cm) x D: 2 in (5.08 cm)

## Top Connection QTHA-3S2F-SS

Materials	Stainless Steel
Seal Materials	Buna-N
Country of origin	USA

## Bottom Connection QTHA-3SSA-LD

Materials	Stainless Steel
Seal Materials	Buna-N
Country of origin	USA

## Fluid Trap TRAP

Max Pressure	3000 PSI / 200 bar / 20 MPa
Max Vacuum	23 InHg / 77.9 kPa
Min Operating Temperature	0 °F / -18 °C
Max Operating Temperature	130 °F / 54 °C
Country of origin	USA
Dimensions	H: 2.2 in (5.59 cm) x W: 2.2 in (5.59 cm) x D: 5.5 in (13.97 cm)