## Solderless Breadboards

#### Breadboards-Powered

## PB-204 Powered Breadboard

Use the PB-204 to construct a wide variety of experiments, including but not limited to:

**Opto-Device Circuits** 

Clocks

Multivibrators

**Oscillator Circuits** 

Timers

**Function Generator Circuits** 

Logic Circuits

Gates

Counters

Flip-Flops

Analog-to-Digital Converters

Digital-to-Analog Converters

Medium Scale Integration Circuits

Phase Lock Loops

Operational Amplifier



#### Features:

Combines utility of a Proto-Board with highly capable regulated DC power supplies

Housed in a rugged metal case

Fixed triple output power supply, 5V @1A, +12V & -12V @ 500mA.

Up to (24) 14-pin DIP IC capacity

Includes three new GS-830, 830 Tie-point Solderless Breadboards & one new GS-080, 80 Tie-point Bus Strip

3-year warranty on all parts and workmanship.

The PB-204 is a durable powered breadboard capable of being used to design a multitude of analog, digital, logic and microcomputer circuits.

The PB-204's on-board power supply eliminates the need for an external supply, adding more versatility to circuit design and experiments, as well as saving valuable bench space by eliminating the need for an external prototyping power supply. Due to its ample sized breadboarding area, the PB-204 is ideally suited to allow for the breadboarding of virtually any type of circuitry, from TTL, CMOS and ECL, to opamps, audio, comparators, video amps, microprocessor components, phase locks and more.

The PB-204's breadboarding area is comprised of Global's "Premium" solderless breadboards and is backed by an industry leading 3-year warranty.

Global Specialties powered breadboards are an important part of the necessary tools required to enable engineers and technicians to train for careers in the rapidly growing field of electronics technology.



Innovative Training Solutions



99 Washington Street Melrose, MA 02176 Phone 781-665-1400 Toll Free 1-800-517-8431



## Solderless Breadboards

### Breadboards-Powered

# Powered Breadboard

## **Specifications**

Model	PB-204
Input power Source	AC Line: 110/120VAC @ 60Hz, or 210-220VAC @ 50Hz
Power Supplies	Fixed DC: +5V +/-0.2VDC, 1.0A max, current limited Load Regulation better than 0.8% +/- 0.02%/°C Ripple, <4mVp-p @1A  Fixed DC: +12VDC, 0.5A max@ +12VDC +/-5% Load Regulation better than 1% +/- 0.04%/°C, Ripple less that 10mVp-p @ 0.5A  Fixed DC: -12VDC, 0.5A max@ +12VDC +/-5% Load Regulation better than 1% +/- 0.04%/°C Ripple less that 10mVp-p @ 0.5A
Binding Posts	(1) Black: Chassis Ground (3) Red: Power Supply Outputs +5VDC, +12VDC & -12VDC
Breadboards	2250 Tie points with (8) 100 pin and (2) 80 pin power rails and accommodates up to 24 (14 pin) IC's
Weight	5lbs 5 oz (2.5kg)
Dimensions	9.8 x 6.6 x3.3" (249 x 167 x 86,7mm)

Technical data subject to change without notice.

#### **Optional Accessories**

**WK-1:** Jumper Wire Kit, 350 pieces **WK-2:** Jumper Wire Kit, 140 pieces **WK-3:** Jumper Wire Kit, 70 pieces

**WK-4:** Wire Jumper Kit, 100 wires with

machined tips

**GSPA Series:** Prototyping adapters **GSPA-K1:** Surface Mount to DIP Adapter

Kit, 6 adapter boards

GSPA-K2: Surface Mount to DIP Adapter

Kit, 11 adapter boards

GSA-3185: Minipro Test Clip Set





99 Washington Street Melrose, MA 02176 Phone 781-665-1400 Toll Free 1-800-517-8431

Visit us at www.TestEquipmentDepot.com