

Trainer Series

Electronic Trainers

PB-501 Logic Design Trainer

Use the PB-501 to construct a wide variety of experiments, including but not limited to:

Logic Gates & Boolean Algebra
Combinational Logic Circuits
Flip-Flops
Counters & Register Circuits
Integrated Logic Circuits
TTL Logic
MOSFETS
CMOS
Interfacing CMOS & TTL
Medium Scale Integration
Decoders
Encoders
Data Conversion & Acquisition



The PB-501 Logic Design Trainer is a low cost portable trainer, which is capable of satisfying many requirements arising in the design and study of digital logic circuitry. The PB-501 can be powered-up via batteries, optional wall-mount power adapter, or by an external 5V power supply. The PB-501 can be utilized for the design and study of gates, counters, multiplexers and can even interface directly to a microprocessor. The PB-501 is housed in a tough molded plastic carrying case with an integral hinged cover which stacks conveniently for storage. Utilizing the PB-501, students will learn valuable hands-on breadboarding techniques and build a solid foundation in digital logic circuit experimentation, construction and analysis.

Features:

- Ideal for digital logic circuit design and experimentation
- Compact design for easy storage
- Includes built-in Clock, Pulsers and Logic Switches
- Premium breadboarding area with 8 power rails
- 3-year warranty on all parts and workmanship.

Global Specialties trainers provide the most complete platform required to enable engineers and technicians to train for careers in the rapidly growing field of electronics technology.



Innovative Training Solutions



99 Washington Street
Melrose, MA 02176
Phone 781-665-1400
Toll Free 1-800-517-8431

Visit us at www.TestEquipmentDepot.com

Logic Design Trainer

Specifications

Model	
	PB-501
Input power Source	Battery - 4 "C" type 6VDC Adapter - Optional External Supplied 5V- Optional
Clock	Frequency - Fixed at 1KHz +/-50% Logic "1" output current 1.2mA @ 3.5V Logic "0" output current 1.2 mA @0.25V User variable with use of external capacitor
Pulsers	Fully debounced pushbuttons (2 each) with logic true and complementary outputs Logic '1" output current 400 μ A @ 2.4V min Logic "0" output current 16mA max @ 0.4V max
Logic Switches	Dual Function: 8 switches buffered by two 4-bit tri-state buffers with separate enables Logic "1" output current 2.6mA max @2.4V min Logic "0" output current 24mA max @ 0.5V max Enables: Logic "1" input current 400 μ A @ 5V Logic "0" input current 20 μ @ 0.2V
Logic Indictors	Dual Function: 8 LEDs driven by two 4-bit latches with separate enables Logic "1" input current 50 μ A @ 5V Logic "0" Input current not required
Breadboards	840 tie points with (8) 25 pin power rails and accommodates up to 8 (14 pin) ICs
Weight	1 lb, 6oz (Minus Batteries & Adapter) (0.5 kg)
Dimensions	10 x 7.5 x 2.6" (254 x 190 x 66 mm)

Technical data subject to change without notice.

Optional Accessories

PB-501 Adapter: 6V Wall Adapter

WK-1: Jumper Wire Kit, 350 pieces

WK-2: Jumper Wire Kit, 140 pieces

WK-3: Jumper Wire Kit, 70 pieces

WK-4: Wire Jumper Kit, 100 wires with machined tips

GSPA Series: Prototyping Adapters

GSPA-K1: Surface mount to DIP Adapter Kit, 6 adapter boards

GSPA-K2: Surface mount to DIP Adapter Kit, 11 adapter boards

GSA-3185: Minipro Test Clip Set



Innovative Training Solutions

© 2011 Global Specialties