

TECHNICAL DATA

PLS 6R, 6G Line and Point Laser Levels PLS 180R, 180G Line Laser Levels





Accuracy

PLS 180R, 180G, PLS 6R, 6G is accurate to ≤1/8 in at 30 ft. (≤3 mm @ 10 m)



Horizontal fan angle: 180 °



Vertical fan angle: 130°



Pendulum lock

The PLS 6 and PLS 180 are equipped with a pendulum lock, ensuring safe transport and the ability to lock the laser level in tilt mode.



IP54

IP 54 rating to limit dust and water entry for years of operation on the job site.



PLS laser levels are backed by a three-year best-in-class warranty, ensuring you don't lose any time on the job. If you experience issues with your PLS tools during the warranty period, except for obvious misuse or damage, your local dealer can provide you a same day replacement tool.

Level. Layout. Build.™

The new PLS 6 and PLS 180 red and green laser levels offer the durability and precision you expect from PLS, a Fluke Company. We've replaced the PLS 4 red with the PLS 6 and created both a red and green version. The fast settling, self-leveling pendulum gives you accurate point and reference lines almost instantly. Additionally, these products feature a pendulum lock to secure the laser during transport or if dropped.

PRODUCT OVERVIEW

All laser level models

- Accuracy: ≤1/8 in at 30 ft. (≤3 mm @ 10 m)
- Durable pendulum lock

PLS 6R, PLS 6G

- Plumb, level, and square with one tool. This professional selfleveling combination point and cross line laser level in red and green includes vertical and horizontal modes with lines and points combined. Great for metal or wood stud installation, general layout, square alignment, or finish carpentry.
- Kit includes floor stand, magnetic L-bracket, and UB9 wall and ceiling bracket for fast, easy overhang and centerline measurements.
- System includes the SLD laser line detector for use in bright lighting, long distances, or outdoors.

PLS 180R, PLS 180G

- This professional self-leveling cross line laser level in both red and green is equipped for multiple applications including wall construction, acoustic ceiling installation, tile installation, residential and commercial construction.
- Kit includes magnetic L-bracket for fast, easy overhang and centerline measurements and the UB9 Universal Wall/Ceiling Bracket for fine vertical adjustment and ceiling installation.
- System includes the SLD laser line detector for use in bright lighting, long distances, or outdoors.

PLS, The Professional Standard— Built by contractors for contractors

PLS lasers provide bright, crisp reference points and lines for quick and accurate layout. As the Professional Standard of laser levels, PLS tools were developed out of necessity by professional contractors with over 50 years of experience in commercial and residential interior and exterior layout. Now, as a Fluke Company, PLS incorporated Fluke's high standards for accuracy, ruggedness, and dependability.





Specifications

Battery Life, Continuous Use Red ≥ 8 hours (both lasers) Green ≥ 3 hours (both lasers) Point Laser Direction (6 only) 90° up, down, left, right Line Fan Angle ≥ 180° Horizontal ≥ 180° Vertical ≥ 130° Working Range Point Laser (6 only) Point Laser (6 only) ≤30 m (100 ft.) Line Laser ≤15 m (50 ft.) With SLD 6 m to 60 m (20 ft. to 200 ft.) Accuracy ≤3 mm @ 10 m (≤1/8 in at 30 ft.) Laser Leveling 3 mm @ 10 m (≤1/8 in at 30 ft.) System Automatic, Pendulum Range 4° Line Laser Width ≤2 mm at 5 m Temperature Operating Operating -10 °C to 50 °C (14 °F to 122 °F) Storage With Batteries With Batteries -18 °C to 50 °C (-0.4 °F to 122 °F) Without Batteries -20 °C to 70 °C (-13 °F to 158 °F)	opeomeations	PLS 6R, 6G PLS 180R, 180G		
Battery Life, Continuous Use Red	Pattoni			
Red ≥ 8 hours (both lasers) Green ≥ 3 hours (both lasers) Point Laser (Bondy) Line Fan Angle Horizontal ≥ 180° Vertical ≥ 180° Vertical ≥ 180° Vertical ≥ 180° Working Range Point Laser (6 only) Line Laser (6 only) Line Laser (6 only) Line Laser (7 only) With SLD 5 6 m to 80 m (20 ft. to 200 ft.) Accuracy ≥ 3 mm @ 10 m (≥1/8 in at 30 ft.) Laser Leveling System Automatic, Pendulum Range 4° Line Laser Width ≥ 2 m and 5 m Temperature Operating 10 °C to 50 °C (14 °F to 122 °F) Storage With Batteries 18 °C to 50 °C (14 °F to 122 °F) Without Batteries 18 °C to 50 °C (14 °F to 122 °F) Without Batteries 19 °C to 70 °C (13 °F to 188 °F) Relative Humidity 0 % 57 5% 68 °C to 40 °C; 0 % to 75 % 68 °C to 40 °C; 0 % to 75 % 68 °C to 40 °C; 0 % to 75 °C (15 °F) Size (H x W x L) 116 mm x 64 mm x 104 mm (4.6 in x 2.5 in x 4.1 in) Weight 10 °C to 80° (10 °C (10 °C) °C; Size (H x W x L) 116 mm x 64 mm x 104 mm (4.6 in x 2.5 in x 4.1 in) Safety 1 EC 61010-15 Pollution Degree 2 Lagin Source Max Output Power Semiconductor Issuer diode Max O	•	3 X AA AIKAIII IE IEC LAO		
Some	• •			
Point Laser Direction (6 only) 190° up, down, left, right Line Fan Angle Horizontal ≥ 180° Vertical ≥ 180° Working Range Point Laser (6 only) Line Laser (6 only) Line Laser (6 only) Line Laser (7 only) With SLD \$15 m (50 fL) With SLD \$10 m (£1/8 in at 30 ft.) Laser Leveling System Automatic, Pendulum Range \$4° Line Laser Width \$2° mm at 5 m Temperature Operating 10 ° ° ° ° C to 50 ° ° C (14 ° F to 122 ° F) Storage With Batteries \$10 m (51 / 8 m ft.) With Batteries \$10 m (51 / 8 m ft.) With Batteries \$10 m (51 / 8 m ft.) With Batteries \$10 m (51 / 8 m ft.) With Batteries \$10 m (51 / 8 m ft.) With Batteries \$10 m (51 / 8 m ft.) With Batteries \$10 m (51 / 8 m ft.) With Batteries \$10 m (51 / 8 m ft.) With Batteries \$10 m (51 / 8 m ft.) With Batteries \$10 m (51 / 8 m ft.) With Batteries \$10 m m m m m m m m m m m m m m m m m m m	Red	≥ 8 hours (both lasers)		
Line Fan Angle Horizontal ≥ 180° Working Range Point Laser (6 only) ≤30 m (100 ft.) Line Laser Without SLD ≤15 m (50 ft.) With SLD 6 m to 60 m (20 ft. to 200 ft.) Accuracy ≤3 mm @ 10 m (≤1/8 in at 30 ft.) Laser Leveling System Automatic, Pendulum Range 4 4° Line Laser Width ≤2 mm at 5 m Temperature Operating -10 °C to 50 °C (-0.4 °F to 122 °F) Storage With Batteries -18 °C to 50 °C (-0.4 °F to 122 °F) Without Batteries -20 °C to 70 °C (-13 °F to 158 °F) Relative Humidity 0 % to 90 % (0 °C to 35 °C) 0 % to 45 % (40 °C to 50 °C) 0 % to 45 % (40 °C to 50 °C) 0 % to 45 % (40 °C to 50 °C) 116 Sarety EC 6100-1; Pollution Degree 2 Light Source Semiconductor laser clide Max Output Power Semiconductor laser clide Max Output Power	Green	≥ 3 hours (both lasers)		
Horizontal ≥ 180°	Point Laser Direction (6 only)	90° up, down, left, right		
Vertical	Line Fan Angle			
Working Range Point Laser (6 only) Line Laser Without SLD S15 m (60 ft.) With SLD 6 m to 60 m (20 ft. to 200 ft.) Accuracy Laser Leveling System Automatic, Pendulum Range 4° Line Laser Width S2 mm at 5 m Temperature Operating Without Batteries Without Batteries Without Batteries Without Batteries -18 °C to 50 °C (-0.4 °F to 122 °F) Storage With Batteries -20 °C to 70 °C (-13 °F to 158 °F) Without Batteries -20 °C to 70 °C (-13 °F to 158 °F) Size (H x W x L) Size (H	Horizontal	≥ 180°		
Point Laser (6 only) Line Laser Without SLD \$ 15 m (50 ft.) With SLD 6 m to 60 m (20 ft. to 200 ft.) Accuracy \$ 3 mm @ 10 m (≤1/8 in at 30 ft.) Laser Leveling System Automatic, Pendulum Range 4° Line Laser Width \$ 2 mm at 5 m Temperature Operating -10 °C to 50 °C (14 °F to 122 °F) Storage With Batteries 48° C to 50 °C (-0.4 °F to 122 °F) Without Batteries -18 °C to 50 °C (-0.4 °F to 122 °F) Without Batteries -20 °C to 70 °C (-13 °F to 158 °F) Relative Humidity 0 % to 90 % (0 °C to 35 °C) 3 % to 40 °C) 9 % to 45 % (40 °C to 50 °C) Size (H x W x L) 116 mm x 64 mm x 104 mm (4.6 in x 2.5 in x 4.1 in) Weight -0.6 kg (1.3 lb.) Safety Laser Light Source Max Output Power Wavelength Red Green Electromagnetic Compatibility (EMC) IEC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class B Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment its directly connected to a test object	Vertical	≥ 130°		
Hine Laser Without SLD With SLD Sam @ 01 om (20 ft. to 200 ft.) Accuracy System Automatic, Pendulum Range Line Laser Width Temperature Operating Storage With Batteries Without Batteries Without Batteries Felative Humidity O % to 90 % (0 ° ℃ to 35 ° ℃ (14 ° F to 122 ° F) Without Batteries Case (1 × × × × × × × × × × × × × × × × × ×	Working Range			
Without SLD ≤15 m (50 ft.) With SLD 6 m to 60 m (20 ft. to 200 ft.) Accuracy ≤3 mm @ 10 m (≤1/8 in at 30 ft.) Laser Leveling System System Automatic, Pendulum Range 4° Line Laser Width ≤2 mm at 5 m Temperature Operating -10 °C to 50 °C (14 °F to 122 °F) Storage With Batteries -18 °C to 50 °C (-0.4 °F to 122 °F) Without Batteries -20 °C to 70 °C (-13 °F to 158 °F) Relative Humidity 0 % to 90 % (0 °C to 35 °C) O % to 7% (35 °C to 40 °C) 0 % to 45 % (40 °C to 50 °C) Size (H x W x L) 116 mm x 64 mm x 104 mm (4.6 in x 2.5 in x 4.1 in) Weight - 0.6 kg (1.3 lb.) Safety IEC 61010-1: Pollution Degree 2 Laser IEC 61010-1: Pollution Degree 2 Light Source Semiconductor laser diode Max Output Power < 1 mW Wavelength 635 nm ± 5 nm Red 635 nm ± 5 nm Green 525 nm ± 5 nm Electromagnetic Compatibility (EMC) International Class B	Point Laser (6 only)	≤30 m (100 ft.)		
Without SLD ≤15 m (50 ft.) With SLD 6 m to 60 m (20 ft. to 200 ft.) Accuracy ≤3 mm @ 10 m (≤1/8 in at 30 ft.) Laser Leveling System System Automatic, Pendulum Range 4° Line Laser Width ≤2 mm at 5 m Temperature Operating Operating -10 °C to 50 °C (14 °F to 122 °F) Storage With Batteries With Batteries -18 °C to 50 °C (-0.4 °F to 122 °F) Without Batteries -20 °C to 70 °C (-13 °F to 158 °F) Relative Humidity 0 % to 75 % (35 °C to 40 °C) O % to 75 % (35 °C to 40 °C) 0 % to 75 % (35 °C to 40 °C) Size (H x W x L) 116 mm x 64 mm x 104 mm (4.6 in x 2.5 in x 4.1 in) Weight -0.6 kg (1.3 lb.) Safety IEC 61010-1: Pollution Degree 2 Laser IEC 61010-1: Pollution Degree 2 Light Source Semiconductor laser diode Max Output Power < 1 mW				
With SLD		<15 m (50 ft)		
Accuracy ≤3 mm @ 10 m (≤1/8 in at 30 ft.) Laser Leveling System Automatic, Pendulum Range 4° Line Laser Width ≤2 mm at 5 m Temperature Operating -10 °C to 50 °C (-0.4 °F to 122 °F) Storage With Batteries -18 °C to 50 °C (-0.4 °F to 122 °F) Without Batteries -20 °C to 70 °C (-13 °F to 158 °F) Relative Humidity 0 % to 90 % (0 °C to 35 °C) 0 % to 75 % (35 °C to 40 °C) 0 % to 75 % (36 °C to 40 °C) 0 % to 75 % (36 °C to 40 °C) 0 % to 45 % (40 °C to 50 °C) Size (H x W x L) 116 mm x 64 mm x 104 mm (4,6 in x 2.5 in x 4.1 in) Weight - 0.6 kg (1.3 lb.) Safety IEC 61010-1: Pollution Degree 2 Laser IEC 60825-1:2014 Class 2 Light Source Semiconductor laser diode Max Output Power < 1 mW Wavelength 635 nm ± 5 nm Red 635 nm ± 5 nm Green EC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class B Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal fun				
System		· · · · · · · · · · · · · · · · · · ·		
Automatic, Pendulum Range 4° Line Laser Width S≥2 mm at 5 m Temperature Operating Operating Storage With Batteries -18 °C to 50 °C (14 °F to 122 °F) Without Batteries -20 °C to 70 °C (-0.4 °F to 122 °F) Without Batteries -20 °C to 70 °C (-13 °F to 158 °F) Relative Humidity 0 % to 90 % (0 °C to 35 °C) 0 % to 75 % (35 °C) 0 % to 45 % (40 °C to 35 °C) Size (H x W x L) Safety 116 mm x 64 mm x 104 mm (4.6 in x 2.5 in x 4.1 in) Weight -0.6 kg (1.3 lb.) Safety Light Source Max Output Power Wavelength Red Green Electromagnetic Compatibility (EMC) IEC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class B Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment itself. Class B: Equipment is suitable for use in domestic establishments ad in establishments directly connected to a levs voltage power supply network which supplies buildings used for domestic purposes. Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a lest object	•	≤5 11 III (€ 10 11 (€ 1/0 11 at 50 1t.)		
Line Laser Width Temperature Operating -10 °C to 50 °C (14 °F to 122 °F) Storage With Batteries Without Batteries -18 °C to 50 °C (-0.4 °F to 122 °F) Without Batteries -18 °C to 50 °C (-0.4 °F to 122 °F) Without Batteries -20 °C to 70 °C (-13 °F to 158 °F) Relative Humidity 0 % to 90 % (0 °C to 35 °C) 0 % to 75 % (35 °C to 40 °C) 0 % to 75 % (35 °C to 40 °C) 0 % to 75 % (35 °C to 40 °C) 0 % to 75 % (35 °C to 40 °C) 0 % to 75 % (40 °C) 0 % to 75 % (35 °C to 40 °C) 0 % to 45 % (40 °C) 10 % to 75 % (35 °C to 40 °C) 0 % to 45 % (40 °C) 10 % to 45 % (40 °C) 116 mm x 64 mm x 104 mm (4.6 in x 2.5 in x 4.1 in) Weight -0.6 kg (1.3 lb.) Safety IEC 61010-1: Pollution Degree 2 Laser IEC 60825-1:2014 Class 2 Light Source Max Output Power Wavelength Red 635 nm ± 5 nm Green Electromagnetic Compatibility (EMC) IEC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class B Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment itself. Class B: Equipment is suitable for use in domestic establishments and in establishments directly connected to a low voltage power supply network which supplies buildings used for domestic purposes. Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a test object				
Line Laser Width Temperature Operating -10 °C to 50 °C (14 °F to 122 °F) Storage With Batteries -18 °C to 50 °C (-0.4 °F to 122 °F) Without Batteries -20 °C to 70 °C (-13 °F to 158 °F) Relative Humidity 0 % to 90 % (0 °C to 35 °C) 0 % to 75 % (35 °C to 40 °C) 0 % to 75 % (35 °C to 40 °C) 0 % to 45 % (40 °C to 50 °C) Size (H x W x L) 116 mm x 64 mm x 104 mm (4.6 in x 2.5 in x 4.1 in) Weight -0.6 kg (1.3 lb.) Safety 1EC 61010-1: Pollution Degree 2 Laser 1EC 68025-1:2014 Class 2 Light Source Max Output Power Wavelength Red Green 525 nm ± 5 nm Electromagnetic Compatibility (EMC) IEC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class B Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment itself. Class B: Equipment is suitable for use in domestic establishments and in establishments directly connected to a low voltage power supply network which supplies buildings used for domestic purposes. Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a test object	•			
Temperature Operating		4°		
Operating Storage With Batteries -18 °C to 50 °C (-0.4 °F to 122 °F) Without Batteries -20 °C to 70 °C (-13 °F to 158 °F) Without Batteries -20 °C to 70 °C (-13 °F to 158 °F) Relative Humidity 0 % to 90 % (0 °C to 35 °C) 0 % to 45 % (40 °C to 50 °C) 0 % to 45 % (40 °C to 50 °C) 0 % to 45 % (40 °C to 50 °C) Size (H x W x L) 116 mm x 64 mm x 104 mm (4.6 in x 2.5 in x 4.1 in) Weight -0.6 kg (1.3 lb.) Safety IEC 61010-1: Pollution Degree 2 Laser IEC 60825-1:2014 Class 2 Light Source Max Output Power Wavelength Red Green Electromagnetic Compatibility (EMC) IEC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class B Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment itself. Class B: Equipment is suitable for use in domestic establishments and in establishments directly connected to a low voltage power supply network which supplies buildings used for domestic purposes. Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to	Line Laser Width	≤2 mm at 5 m		
Storage With Batteries -18 °C to 50 °C (-0.4 °F to 122 °F) Without Batteries -20 °C to 70 °C (-13 °F to 158 °F) Relative Humidity 0 % to 90 % (0 °C to 35 °C) 0 % to 75 % (35 °C to 40 °C) 0 % to 45 % (40 °C to 50 °C) Size (H x W x L) 116 mm x 64 mm x 104 mm (4.6 in x 2.5 in x 4.1 in) Weight -0.6 kg (1.3 lb.) Safety IEC 61010-1: Pollution Degree 2 Laser IEC 60825-1:2014 Class 2 Light Source Semiconductor laser diode Max Output Power Wavelength Red 635 nm ± 5 nm Green Electromagnetic Compatibility (EMC) IEC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class B Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment itself. International Class B: Equipment is suitable for use in domestic establishments and in establishments directly connected to a low voltage power supply network which supplies buildings used for domestic purposes. Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to	Temperature			
With Batteries -18 °C to 50 °C (-0.4 °F to 122 °F) Without Batteries -20 °C to 70 °C (-13 °F to 158 °F) Relative Humidity 0 % to 90 % (0 °C to 35 °C) 0 % to 75 % (35 °C to 40 °C) 0 % to 75 % (35 °C to 40 °C) 0 % to 45 % (40 °C to 50 °C) Size (H x W x L) 116 mm x 64 mm x 104 mm (4.6 in x 2.5 in x 4.1 in) Weight -0.6 kg (1.3 lb.) Safety IEC 61010-1: Pollution Degree 2 Laser IEC 60825-1:2014 Class 2 Light Source Max Output Power Vavelength Red 635 nm ± 5 nm Green Electromagnetic Compatibility (EMC) IEC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class B Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment itself. Class B: Equipment is suitable for use in domestic establishments and in establishments directly connected to a low voltage power supply network which supplies buildings used for domestic purposes. Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a test object	Operating	-10 °C to 50 °C (14 °F to 122 °F)		
Without Batteries Relative Humidity 0 % to 90 % (0 °C to 35 °C) 0 % to 75 % (35 °C to 40 °C) 0 % to 45 % (40 °C to 50 °C) 0 % to 45 % (40 °C to 50 °C) Size (H x W x L) 116 mm x 64 mm x 104 mm (4.6 in x 2.5 in x 4.1 in) Weight -0.6 kg (1.3 lb.) Safety Laser 1EC 61010-1: Pollution Degree 2 Laser 1EC 60825-1:2014 Class 2 Light Source Max Output Power Wavelength Red Green 525 nm ± 5 nm Electromagnetic Compatibility (EMC) IEC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class B Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment itself. Class B: Equipment is suitable for use in domestic establishments and in establishments directly connected to a low voltage power supply network which supplies buildings used for domestic purposes. Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a test object	Storage			
Relative Humidity 0 % to 90 % (0 °C to 35 °C) 0 % to 75 % (35 °C to 40 °C) 0 % to 75 % (35 °C to 40 °C) 0 % to 45 % (40 °C to 50 °C) Size (H x W x L) 116 mm x 64 mm x 104 mm (4.6 in x 2.5 in x 4.1 in) Weight - 0.6 kg (1.3 lb.) Safety IEC 61010-1: Pollution Degree 2 Laser IEC 60825-1:2014 Class 2 Light Source Max Output Power Wavelength Red Green 635 nm ± 5 nm Green Flectromagnetic Compatibility (EMC) IEC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class B Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment itself. Class B: Equipment is suitable for use in domestic establishments and in establishments directly connected to a low voltage power supply network which supplies buildings used for domestic purposes. Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a test object	With Batteries	-18 °C to 50 °C (-0.4 °F to 122 °F)		
Class B: Equipment is suitable for use in domestic establishments and in establishments directly connected to a lest object	Without Batteries	-20 °C to 70 °C (-13 °F to 158 °F)		
Size (H x W x L) Size (H x W x L) 116 mm x 64 mm x 104 mm (4.6 in x 2.5 in x 4.1 in) Weight - 0.6 kg (1.3 lb.) Safety IEC 61010-1: Pollution Degree 2 Laser IEC 60825-1:2014 Class 2 Light Source Max Output Power Max Output Power Wavelength Red Green 635 nm ± 5 nm Green Flectromagnetic Compatibility (EMC) IEC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class B Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment itself. Class B: Equipment is suitable for use in domestic establishments and in establishments directly connected to a low voltage power supply network which supplies buildings used for domestic purposes. Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a test object	Relative Humidity	0 % to 90 % (0 °C to 35 °C)		
Size (H x W x L) Weight Co.6 kg (1.3 lb.) Safety IEC 61010-1: Pollution Degree 2 Laser IEC 60825-1:2014 Class 2 Light Source Max Output Power Wavelength Red Green Electromagnetic Compatibility (EMC) IEC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class B Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment is suitable for use in domestic establishments and in establishments directly connected to a low voltage power supply network which supplies buildings used for domestic purposes. Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a test object				
Weight ~ 0.6 kg (1.3 lb.) Safety IEC 61010-1: Pollution Degree 2 Laser IEC 60825-1:2014 Class 2 Light Source Semiconductor laser diode Max Output Power < 1 mW Wavelength Red 635 nm ± 5 nm Green 525 nm ± 5 nm Electromagnetic Compatibility (EMC) IEC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class B Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment itself. International Class B: Equipment is suitable for use in domestic establishments and in establishments directly connected to a low voltage power supply network which supplies buildings used for domestic purposes. Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a test object	Size (H x W x I)			
Safety IEC 61010-1: Pollution Degree 2				
Light Source Max Output Power Wavelength Red Green Electromagnetic Compatibility (EMC) EC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class B Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment itself. International Class B: Equipment is suitable for use in domestic establishments and in establishments directly connected to a low voltage power supply network which supplies buildings used for domestic purposes. Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a test object		9, ,		
Max Output Power Wavelength Red Green Electromagnetic Compatibility (EMC) IEC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class B Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment itself. International Class B: Equipment is suitable for use in domestic establishments and in establishments directly connected to a low voltage power supply network which supplies buildings used for domestic purposes. Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a test object				
Wavelength Red 635 nm ± 5 nm Green 525 nm ± 5 nm Electromagnetic Compatibility (EMC) IEC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class B Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment itself. International Class B: Equipment is suitable for use in domestic establishments and in establishments directly connected to a low voltage power supply network which supplies buildings used for domestic purposes. Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a test object	•			
Red 535 nm ± 5 nm Green 525 nm ± 5 nm Electromagnetic Compatibility (EMC) IEC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class B Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment itself. International Class B: Equipment is suitable for use in domestic establishments and in establishments directly connected to a low voltage power supply network which supplies buildings used for domestic purposes. Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a test object	•	< 1 HIVV		
Green Electromagnetic Compatibility (EMC) IEC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class B Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment itself. International Class B: Equipment is suitable for use in domestic establishments and in establishments directly connected to a low voltage power supply network which supplies buildings used for domestic purposes. Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a test object	9	635 nm + 5 nm		
IEC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class B Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment itself. International Class B: Equipment is suitable for use in domestic establishments and in establishments directly connected to a low voltage power supply network which supplies buildings used for domestic purposes. Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a test object				
Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment itself. Class B: Equipment is suitable for use in domestic establishments and in establishments directly connected to a low voltage power supply network which supplies buildings used for domestic purposes. Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a test object	Electromagnetic Compatibility (EMC)		
Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment itself. Class B: Equipment is suitable for use in domestic establishments and in establishments directly connected to a low voltage power supply network which supplies buildings used for domestic purposes. Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a test object		IEC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class B		
International Class B: Equipment is suitable for use in domestic establishments and in establishments directly connected to a low voltage power supply network which supplies buildings used for domestic purposes. Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a test object		Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy		
Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a test object	International	Class B: Equipment is suitable for use in domestic establishments and in establishments directly con-		
Korea (KCC) Class B Equipment (Broadcast communications equipment for home)		Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to		
(Korea (KCC)	Class B Equipment (Broadcast communications equipment for home)		
USA (FCC) 47 CFR 15 subpart B. This product is considered an exempt device per clause 15.103.				





Ordering information

Laser levels						
Part number	SKU	Item description	What's in the box			
5009423	PLS 6R Z	Cross Line and Point Red Laser Bare Tool	PLS 6R laser level, PLS canvas pouch, PLS BP5 alkaline battery pack, Safety Sheet and Quick Reference Guide			
5009438	PLS 6R KIT	Cross Line and Point Red Laser Kit	PLS 6R laser level, PLS canvas pouch, PLS BP5 alkaline battery pack, PLS UB9 Universal Ceiling and Wall Bracket, PLS FS Floor Stand, PLS MLB Magnetic L-Bracket, PLS RRT4 Red Reflective Target, Safety Sheet and Quick Reference Guide			
5009445	PLS 6R SYS	Cross Line and Point Red Laser System	PLS 6R laser level, PLS canvas pouch, PLS BP5 alkaline battery pack, PLS SLD-RED Red Laser Line Detector, PLS 60520 SLD Clamp, PLS UB9 Universal Ceiling and Wall Bracket, PLS FS Floor Stand, PLS MLB Magnetic L-Bracket, PLS RRT4 Red Reflective Target, Safety Sheet and Quick Reference Guide			
5009461	PLS 6G Z	Cross Line and Point Green Bare Tool	PLS 6G laser level, PLS canvas pouch, PLS BP5 alkaline battery pack, Safety Sheet and Quick Reference Guide			
5009489	PLS 6G KIT	Cross Line and Point Green Laser Kit	PLS 6G laser level, PLS canvas pouch, PLS BP5 alkaline battery pack, PLS UB9 Universal Ceiling and Wall Bracket, PLS FS Floor Stand, PLS MLB Magnetic L-Bracket, PLS GRT4 Green Reflective Target, Safety Sheet and Quick Reference Guide			
5009492	PLS 6G SYS	Cross Line and Point Green Laser System	PLS 6G laser level, PLS canvas pouch, PLS BP5 alkaline battery pack, PLS SLD-GREEN Green Laser Line Detector, PLS 60520 SLD Clamp, PLS UB9 Universal Ceiling and Wall Bracket, PLS FS Floor Stand, PLS MLB Magnetic L-Bracket, PLS GRT4 Green Reflective Target, Safety Sheet and Quick Reference Guide			
5017279	PLS 180R Z	Cross Line Red Laser Bare Tool	PLS 180R laser level, PLS canvas pouch, PLS BP5 alkaline battery pack, Safety Sheet and Quick Reference Guide			
5009450	PLS 180R KIT	Cross Line Red Laser Kit	PLS 180R laser level, PLS canvas pouch, PLS BP5 alkaline battery pack, PLS UB9 Universal Ceiling and Wall Bracket, PLS FS Floor Stand, PLS MLB Magnetic L-Bracket, PLS RRT4 Red Reflective Target, Safety Sheet and Quick Reference Guide			
5019428	PLS 180R SYS	Cross Line Red Laser System	PLS 180R laser level, PLS canvas pouch, PLS BP5 alkaline battery pack, PLS SLD-RED Red Laser Line Detector, PLS 60520 SLD Clamp, PLS UB9 Universal Ceiling and Wall Bracket, PLS FS Floor Stand, PLS MLB Magnetic L-Bracket, PLS RRT4 Red Reflective Target, Safety Sheet and Quick Reference Guide			
5017287	PLS 180G Z	Cross Line Green Laser Bare Tool	PLS 180G laser level, PLS canvas pouch, PLS BP5 alkaline battery pack, Safety Sheet and Quick Reference Guide			
5009509	PLS 180G KIT	Cross Line Green Laser Kit	PLS 180G laser level, PLS canvas pouch, PLS BP5 alkaline battery pack, PLS UB9 Universal Ceiling and Wall Bracket, PLS FS Floor Stand, PLS MLB Magnetic L-Bracket, PLS GRT4 Green Reflective Target, Safety Sheet and Quick Reference Guide			
5019437	PLS 180G SYS	Cross Line Green Laser System	PLS 180G laser level, PLS canvas pouch, PLS BP5 alkaline battery pack, PLS SLD-GREEN Green Laser Line Detector, PLS 60520 SLD Clamp, PLS UB9 Universal Ceiling and Wall Bracket, PLS FS Floor Stand, PLS MLB Magnetic L-Bracket, PLS GRT4 Green Reflective Target, Safety Sheet and Quick Reference Guide			



Ordering information

Ordering information						
Accessories						
Part number	SKU	Item description	What's in the box			
4792193	PLS-60573	PLS Pouch, Canvas	PLS Pouch, Canvas			
5031929	PLS FS	Floor Stand for PLS 3, 5, 6	PLS FS Floor Stand			
5031934	PLS MLB	Magnetic L-Bracket, PLS 3, 5, 6, 180	PLS MLB Magnetic L-Bracket			
5031952	PLS BP5	BP5 Alkaline Battery Pack	PLS BP5 Alkaline Battery Pack			
4966636	PLS UB9	UB9 Universal Ceiling/Wall Bracket	PLS UB9, Quick Reference Guide			
4978515	PLS SLD RED	SLD Red Detector W/ Bracket	PLSPLS 60520 SLD clamp, Battery, Quick Reference Guide			
4978526	PLS SLD GREEN	SLD Green Detector W/ Bracket	PLSPLS 60520 SLD clamp, Battery, Quick Reference Guide			
5022629	PLS RRT4	Red Magnetic Reflective Target	RRT4 red reflective target			
5022634	PLS GRT4	Green Magnetic Reflective Target	GRT4 green reflective target			
4985124	PLS C18	Laser Level Tool Box	PLS C18 Laser Level Tool Box			

