


		MODELS 48/49/49HT		PRE-INSULATED CRIMP WIRE-NUT® WIRE CONNETORS																					
FEATURES/BENEFITS:																									
		-WIDE WIRE RANGE ENABLES USE ON VARIETY OF APPLICATIONS -NEW, COMPACT DESIGN FITS EASILY INTO TIGHT LOCATIONS -SLIGHTLY FLARED SKIRT PROTECTS AGAINST TURNED-BACK STRANDS WITHOUT TAKING UP VALUABLE SPACE -BEVELED ENTRY HELPS GUIDE CONDUCTORS INTO THE CONNECTOR BODY FOR REDUCED CONNECTION TIME																							
ELECTRICAL:			APPLICATION TOOLING:																						
VOLTAGE: 600 V MAX* *SIGNS/LUMINARES 1000V			- Pneumatic Crimp Tool - PCAM™ (Pre-Insulated Crimp Application Machine) - Crimpmaster™ Hand Tool																						
PHYSICAL:			STANDARDS & SPECIFICATIONS:																						
HOUSING: NYLON INSERT: COPPER PLATING: TIN TEMPERATURE: - MODEL 48/49 105 C (221 F) - MODEL 49HT 150 C (302 F)			UL 486C UL 94V-2 FLAME RATING CSA-C22.2 NO. 188 RoHS COMPLAINT																						
WIRE RANGE: - Solid and/or stranded wire combinations unless stated otherwise - Consult factory for other combinations not listed																									
MODEL			MODEL 49 & 49HT																						
STRIP LENGTH: 3/8" (9,5mm)			STRIP LENGTH: 3/8" (9,5mm)																						
1 or 3 #16 1 to 4 #18 1 to 5 #20 1 to 6 #22			1 to 2 #14 1 to 4 #16 1 to 6 #18 1 to 6 #20																						
DIMENSIONS:																									
				<table><tr><th>MODEL</th><th>A (in)</th><th>A (mm)</th><th>B (in)</th><th>B (mm)</th></tr><tr><td>48</td><td>0.36</td><td>9,1</td><td>0.75</td><td>19</td></tr><tr><td>49</td><td>0.47</td><td>11,9</td><td>0.82</td><td>20,8</td></tr><tr><td>49HT</td><td>0.47</td><td>11,9</td><td>0.82</td><td>20,8</td></tr></table>		MODEL	A (in)	A (mm)	B (in)	B (mm)	48	0.36	9,1	0.75	19	49	0.47	11,9	0.82	20,8	49HT	0.47	11,9	0.82	20,8
MODEL	A (in)	A (mm)	B (in)	B (mm)																					
48	0.36	9,1	0.75	19																					
49	0.47	11,9	0.82	20,8																					
49HT	0.47	11,9	0.82	20,8																					
ORDERING INFO:																									
CATALOG #	MODEL	COLOR	QUANTITY:	WEIGHT LBS (KG):																					
30-645	48	White	10,000	15.0 (6.8)																					
30-649	49	White	10,000	27.0 (12.3)																					
30-849	49HT	Grey	10,000	27.0 (12.3)																					