



### ***Affordable Balance to Achieve Reliable Results***

The Pioneer PX combines essential weighing functionality with competitive performance, offering high accuracy and repeatability for applications in laboratory, industrial and education settings. The PX is affordably priced, intuitively designed for intelligent operation with a second line display for additional information, and USB and RS-232 connectivity for easy communication.

#### ***Unique Features Include:***

- The PX offers high accuracy and repeatability for essential weighing applications in laboratory, industrial and education settings at an economical price point.
- Featuring a cast metal lower housing, sub-pan and stainless steel weighing pan, the PX is durably constructed for versatile, long-term use.
- PX features a second line display for additional information/guidance, & USB/RS232 connectivity for easy communication. Draftshield models feature a static removal (ESR) bar for convenient grounding.

# PIONEER® *Semi-Micro, Analytical and Precision Balances*

Durably constructed of cast metal lower housing, metal sub-pan and stainless steel weighing pan for long-term use.

A static removal bar (constructed of permanent static electric dissipative ABS) provides a convenient grounding location.

RS-232 and USB device ports allow for easy connectivity to PCs and PLCs. Equipped with a security lock to prevent unauthorized use.



Large viewing angle with bright backlit LCD display.

Two line display provides additional information or guidance prompts to the user.

Four quick keys enable easy operation of multiple weighing modes.




InCal™ Models	PX85*	PX225D*	PX84	PX124	PX224	PX163	PX323	PX523	PX623
<b>ExCal Models</b>			PX84/E	PX124/E	PX224/E	PX163/E	PX323/E	PX523/E	PX623/E
Capacity (g)	82	82/220	82	120	220	160	320	520	620
Readability d, Fine Range (g)		0.00001		-			-		
Readability d, Full Range (g)	0.00001	0.0001		0.0001			0.001		
Repeatability (sd.), ≤5% of Full Load (g)		0.00001		0.00008			0.0008		
Repeatability (sd.), 5% of Full Load to Fine Range Max (g)		0.00002		-			-		
Repeatability (sd.), Fine Range Max to Full Range (g)	0.00002	0.0001		0.0001			0.001		
Linearity deviation, Typical (g)		± 0.00006		±0.00006			± 0.0006		
Linearity deviation (g)		± 0.0001		± 0.0002			± 0.002		
Stabilization Time (s)		10		3			2		
Units	Milligram, Gram, Kilogram, Ounce, Pound, Carat, Pennyweight, Troy Ounce, Grain, Newton, Hong Kong Tael, Singapore Tael, Taiwan Tael, Momme, Tical (MM), Mesghal, Tola (India), Baht, 1 custom unit								
Applications	Basic Weighing, Parts Counting, Percent Weighing, Animal Weighing, Density Determination								
Pan Size (Ø)	3.15 in. / 80 mm		3.54 in. / 90 mm			4.72 in. / 120 mm			
Draftshield Size	6.8 × 5.2 × 8.1 in. / 172 × 131 × 205 mm								
Power Supply	Power Input: 100–240V ~ 200mA 50–60Hz 12–18VA Power Output: 12 VDC 0.5A								
Assembled Dimensions (W × D × H)	8.2 × 12.6 × 12.2 in. / 209 × 321 × 309 mm								
Operating Conditions	Operating conditions for ordinary lab application: 50° F to 86° F / +10 to 30° C (operability guaranteed between +5 and 40° C)								
Storage Conditions	14° F to 140° F / -10° C to 60° C at 10% to 90% relative humidity, non-condensing								
Net Weight	10 lb / 4.5 kg								
Shipping Weight	15.4 lb / 7 kg								
Shipping Dimensions (W × D × H)	21.7 × 15.2 × 11.5 in. / 507 × 387 × 531 mm								

\*Automatic Calibration models

# PIONEER® *Semi-Micro, Analytical and Precision Balances*

RS-232 and USB device ports allow for easy connectivity to PCs and PLCs. Equipped with a security lock to prevent unauthorized use.



Large viewing angle with bright backlit LCD display.

Two line display provides additional information or guidance prompts to the user.


Four quick keys enable easy operation of multiple weighing modes.



InCal™ Models	PX1602	PX2202	PX3202	PX4202	PX6202	PX2201	PX4201
ExCal Models	PX1602/E	PX2202/E	PX3202/E	PX4202/E	PX6202/E	PX2201/E	PX4201/E
Capacity (g)	1600	2200	3200	4200	6200	2200	4200
Readability (g)	0.01			0.1			
Repeatability (sd.), ≤5% of Full Load (g)	0.008			0.08			
Repeatability (sd. ), 5% of Full Load to Full Range (g)	0.01			0.1			
Linearity deviation, Typical (g)	± 0.006			± 0.06			
Linearity deviation (g)	± 0.02			± 0.2			
Stabilization Time (s)	1						
Units	Milligram, Gram, Kilogram, Ounce, Pound, Carat, Pennyweight, Troy Ounce, Grain, Newton, Hong Kong Tael, Singapore Tael, Taiwan Tael, Momme, Tical (MM), Mesghal, Tola (India), Baht, 1 custom unit						
Applications	Basic Weighing, Parts Counting, Percent Weighing, Animal Weighing, Density Determination						
Pan Size (Ø)	7.09 in. / 180 mm						
Draftshield Size	N/A						
Power Supply	Power Input: 100–240V ~ 200mA 50–60Hz 12–18VA Power Output: 12 VDC 0.5A						
Assembled Dimensions (W × D × H)	8.2 × 12.6 × 3.9 in. / 209 × 321 × 98 mm						
Operating Conditions	Operating conditions for ordinary lab application: 50° F to 86° F / +10 to 30° C (operability guaranteed between +5 and 40° C)						
Storage Conditions	14° F to 140° F / -10° C to 60° C at 10% to 90% relative humidity, non-condensing						
Net Weight	7.7 lb / 3.5 kg						
Shipping Weight	11 lb / 5 kg						
Shipping Dimensions (W × D × H)	21.7 × 15.2 × 11.5 in. / 550 × 385 × 291 mm						

# PIONEER® *Semi-Micro, Analytical and Precision Balances*

## Outline Dimensions



## Other Standard Features and Equipment

Metal base, plastic top housing, removable stainless steel pan, removable glass draftshield or side doors, Real Time Clock with GLP/GMP Data, integrated weigh-below-hook, security bracket, calibration lock and in-use cover, user-selectable environmental filters and brightness settings, auto-tare, auto-dim, user-selectable span calibration points, overload indicator, software lockout and reset menu, user-selectable communication settings and data print options, user-definable project and user IDs, software overload/underload indicator, stability indicator, 11 operating languages

## Compliance

- **Product Safety:** IEC/EN 61010-1; CAN/CSA C22.2 61010-1; UL 61010-1
- **Electromagnetic Compatibility:** IEC/EN 61326-1 Class B, Basic Environments; FCC Part 15 Class A; Canada ICES-003 Class A
- **Compliance Marks:** CSA

## Accessories

Auxiliary Display .....	30472064
Density Kit .....	80253384
Sinker Glass for Density Determination.....	83034024
USB Interface Cable .....	83021085
Security Device .....	80850043
RS-232 Cable (25-pin) .....	80500524
RS-232 Cable (9-pin).....	80500525
Dust Cover .....	30093334
In-Use Cover .....	30372546
Printer SF40A .....	30064203
ION-100A .....	30130302

80775267\_J 20211115 © Copyright OHAUS Corporation

