

Part No.

QTCM-3KPSIG-D

QTCM manifold, 3000 PSIG digital gauge, 20ft, 2ft hoses, (2) 1/4" MNPT process conn., nylon bag

Perform static pressure calibrations using nitrogen with included calibration manifold, pressure gauge and hoses



QTCM-3KPSIG-D

Included Items

- Manifold - QTCM Brass Calibration Manifold (QTCM)
- Pressure Reference - LC10 pressure gauge, 3000 psi / 200 bar / 20 MPa, 1/4" Male NPT bottom connection (LC10-GR2M)
- Reference Connection - 1/4" female NPT x female Quick-test, no check-valve, brass (QTHA-2FBA)
- Process Connection 1 - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Process Connection 2 - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Hose 1 - Quick-test 6900 psi hose, brass hose ends, 20 ft (6.10 m) long (QTQT-HOS-20ft)
- Hose 2 - Quick-test 6900 psi hose, brass hose ends, 2 ft (61 cm) long (QTQT-HOS-2ft)
- Nylon bag - Zippered bag to hold hose and adapters, nylon (QTHA-HSBG)

Specs/Attributes

Materials	Brass
Seal Materials	Buna-N, Delrin, Teflon
Max Pressure	3000 PSI / 200 bar / 20 MPa
Min Operating Temperature	0 °F / -18 °C
Max Operating Temperature	130 °F / 54 °C
Hose 1	Quick-test Hose, Brass ends, 20ft / 6.1m long
Hose 2	Quick-test Hose, Brass ends, 2ft / 0.6m long

Specs/Attributes

Pressure Reference	Digital pressure gauge, 3000 PSIG Pressure
Process Connection	1/4" Male NPT
Reference Connection	1/4" Female NPT
Country of origin	USA
Weight	2.71 lbs / 1.23 kg
Dimensions	H: 7.88 in (20.02 cm) x W: 5 in (12.7 cm) x D: 3.78 in (9.6 cm)

Manifold QTCM

Max Pressure	3000 PSI / 200 bar / 20 MPa
Min Operating Temperature	0 °F / -18 °C
Max Operating Temperature	130 °F / 54 °C
Fine Adjustment Resolution	0.10 PSI / 0.69 mbar / 0.00 kPa
Country of origin	USA
Pressure Media	Nitrogen, inert gas
Inlet Port	Male Quick-test
Materials	Anodized Aluminum, Brass
Media Compatibility	Air, Inert Gas, Natural Gas
Outlet Port	Male Quick-test
Seal Materials	Buna-N, Delrin, Teflon
Burst Pressure	12000 PSI / 825 bar / 83 MPa
Weight	2.20 lbs / 1000 grams
Dimensions	H: 3.8 in (9.65 cm) x W: 5.1 in (12.95 cm) x D: 2.3 in (5.84 cm)

Pressure Reference LC10-GR2M

Battery Count	2
Battery Life	1500 Hours
Battery Type	AA Alkaline (LR6)
Burst Pressure	12000 PSI / 825 bar / 83 MPa
Certifications	Certified to CSA Standard C22.2 No. 61010-1, Conforms to UL / IEC / EN / AS Standard No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU
Country of origin	USA
Electrical Rating	50 mA @ 5 VDC
Engineering Units	atm, bar, cmH2O @4°C, inH2O @39°C, kPa, MPa, psi, inHg @39°F, kgf / cm ² , ftH2O @39°F, cmHg @ 0°C, oz / sqin
Ingress Protection	IP67 (1 meter water submersion for 30 minutes)
LCD Display	2.4 in / 61 mm segmented LCD Display
Materials	ABS / Polycarbonate Blend, Powder Coated Aluminum
Max Operating Temperature	120 °F / 50 °C

Pressure Reference LC10-GR2M

Max Pressure	3000 PSI / 200 bar / 20 MPa
Max Storage Temperature	165 °F / 75 °C
Measurement Type	Gauge Pressure
Media Compatibility	Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Mineral Oil, Natural Gas, Petroleum Based Oil, Skydrol, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil, Water
Min Operating Temperature	-4 °F / -20 °C
Min Storage Temperature	-40 °F / -40 °C
Operating Altitude (max)	10,000 ft (3050 m)
Pressure Measurement Uncertainty	+/- 0.25% of Full Scale (ASME Grade 3A/ISO Class 0.25)
Process Connection	1/4" Male NPT
Protection Class	Pollution Degree 2 (UL / IEC 61010-1)
Relative Humidity	0% to 90% (-10 to 35 °C) , 0% to 70% (35 to 50 °C)
Sensor Type	Pressure Sensor
USB Connection	USB (Micro B)
Wetted Materials	316 Stainless Steel
Wrench Size	7/8 In 23 mm
Weight	12.6 oz / 355 grams
Dimensions	H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 4.1 in (10.41 cm)

Reference Connection QTHA-2FBA

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Wrench Size	3/4 In 19 mm
Dimensions	H: 1.52 in (3.86 cm) x W: 0.75 in (1.91 cm)

Process Connection 1 QTHA-2MB0

Burst Pressure	20000 PSI / 1380 bar / 140 MPa
Country of origin	USA
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa

Process Connection 1 QTHA-2MB0

Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm)

Process Connection 2 QTHA-2MB0

Burst Pressure	20000 PSI / 1380 bar / 140 MPa
Country of origin	USA
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm)

Hose 1 QTQT-HOS-20ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Inner Diameter	0.08 In / 3.00 mm
Length	20 ft / 7.00 m
Materials	Brass
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT

Hose 2 QTQT-HOS-2ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
----------------	--------------------------------

Hose 2 QTQT-HOS-2ft

Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Inner Diameter	0.08 In / 3.00 mm
Length	2 ft / 61 cm
Materials	Brass
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT

Nylon bag QTHA-HSBG

Max Pressure	0.00 PSI / 0.00 mbar / 0.00 kPa
Max Vacuum	0.00 InHg / 0.0 kPa
Materials	Zippered Nylon
Country of origin	USA