

Part No.

QTHA-KIT4-SS

Universal Quick-test hose and adapter kit (20 stainless steel adapters, 2 hoses)

Kits take the guesswork out of selecting adapters by providing a selection of the most popular combinations of hoses and adapters



QTHA-KIT4-SS

Included Items

- 1/8" male NPT adapter, S.S. - 1/8" male NPT x male Quick-test, no check-valve, S.S. (QTHA-1MS0)
- 1/8" male NPT Quick-connect adapter, S.S. - 1/8" male NPT QD (Quick-connect) Adapter, S.S. (QTHA-1MS0-QD)
- 1/4" male NPT adapter, S.S. - 1/4" male NPT x male Quick-test, no check-valve, S.S. (QTHA-2MS0)
- 1/4" male NPT Quick-connect adapter, S.S. - 1/4" male NPT QD (Quick-connect) Adapter, S.S. (QTHA-2MS0-QD)
- 3/8" male NPT adapter, S.S. - 3/8" male NPT x male Quick-test, no check-valve, S.S. (QTHA-3MS0)
- 1/2" male NPT adapter, S.S. - 1/2" male NPT x male Quick-test, no check-valve, S.S. (QTHA-4MS0)
- 1/8" female NPT adapter, S.S. - 1/8" female NPT x male Quick-test, no check-valve, S.S. (QTHA-1FS0)
- 1/8" female Quick-connect adapter, S.S. - 1/8" female NPT Quick-connect x male Quick-test, no check-valve, S.S. (QTHA-1FS0-QD)
- 1/4" female NPT adapter, S.S. - 1/4" female NPT x male Quick-test, no check-valve, S.S. (QTHA-2FS0)
- 1/4" female NPT Quick-connect adapter, S.S. - 1/4" female NPT Quick-connect x male Quick-test, no check-valve, S.S. (QTHA-2FS0-QD)
- 3/8" female NPT adapter, S.S. - 3/8" female NPT x male Quick-test, no check-valve, S.S. (QTHA-3FS0)
- 1/2" female NPT adapter, S.S. - 1/2" female NPT x male Quick-test, no check-valve, S.S. (QTHA-4FS0)
- 1/2" female NPT Quick-connect adapter, S.S. - 1/2" female NPT Quick-connect x male Quick-test, no check-valve, S.S. (QTHA-4FS0-QD)
- 1/4" tube adapter, S.S. - 1/4" tube fitting x male Quick-test, no check-valve, S.S. (QTHA-2TS0)
- 3/8" tube adapter, S.S. - 3/8" tube fitting x male Quick-test, no check-valve, S.S. (QTHA-3TS0)
- 1/2" tube adapter, S.S. - 1/2" tube fitting x male Quick-test, no check-valve, S.S. (QTHA-4TS0)
- 5/16-24 UNF DP Transmitter adapter, S.S. - 5/16"-24 UNF x male Quick-test, no check-valve, S.S. (QTHA-FRS0)
- 1/4-28 UNF DP Transmitter adapter, S.S. - 1/4"-28 UNF X male Quick-test, no check-valve, S.S. (QTHA-HNS0)
- Quick-test tee, S.S. - Male Quick-test run x male Quick-test run x male Quick-test branch tee, S.S. (QTHA-HSTS)
- Male Quick-test union, S.S. - Male Quick-test x male Quick-test hose union, S.S. (QTHA-HHSU)
- Quick-test hose, S.S. ends, 6ft long - Quick-test 6900 psi hose, S.S. hose ends, 6 ft (1.83 m) long (QSQS-HOS-6ft)
- Quick-test hose, S.S. ends, 3ft long - Quick-test 6900 psi hose, S.S. hose ends, 3 ft (92 cm) long (QSQS-HOS-3ft)

Specs/Attributes

Materials	Stainless Steel
Seal Materials	Buna-N, Teflon
Country of origin	USA

1/8" male NPT adapter, S.S. QTHA-1MS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Dimensions	H: 1.2 in (3.05 cm) x W: 0.56 in (1.42 cm)

1/8" male NPT Quick-connect adapter, S.S. QTHA-1MS0-QD

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Teflon
Dimensions	H: 1.75 in (4.45 cm) x W: 0.87 in (2.21 cm)

1/4" male NPT adapter, S.S. QTHA-2MS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm

1/4" male NPT adapter, S.S. QTHA-2MS0

Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm)
------------	---

1/4" male NPT Quick-connect adapter, S.S. QTHA-2MS0-QD

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Seal Materials	Buna-N, Teflon
Dimensions	H: 1.88 in (4.78 cm) x W: 1 in (2.54 cm)

3/8" male NPT adapter, S.S. QTHA-3MS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	3/4 In 19 mm
Dimensions	H: 1.4 in (3.56 cm) x W: 0.75 in (1.91 cm)

1/2" male NPT adapter, S.S. QTHA-4MS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	7/8 In 23 mm
Dimensions	H: 1.57 in (3.99 cm) x W: 0.87 in (2.21 cm)

1/8" female NPT adapter, S.S. QTHA-1FS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel

1/8" female NPT adapter, S.S. QTHA-1FS0

Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N
Wrench Size	5/8 In 16 mm
Dimensions	H: 1.38 in (3.51 cm) x W: 0.62 in (1.57 cm)

1/8" female Quick-connect adapter, S.S. QTHA-1FS0-QD

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Teflon
Dimensions	H: 1.52 in (3.86 cm) x W: 0.78 in (1.98 cm)

1/4" female NPT adapter, S.S. QTHA-2FS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N
Wrench Size	3/4 In 19 mm
Dimensions	H: 1.57 in (3.99 cm) x W: 0.75 in (1.91 cm)

1/4" female NPT Quick-connect adapter, S.S. QTHA-2FS0-QD

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa

1/4" female NPT Quick-connect adapter, S.S. QTHA-2FS0-QD

Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Teflon
Dimensions	H: 1.67 in (4.24 cm) x W: 0.94 in (2.39 cm)

3/8" female NPT adapter, S.S. QTHA-3FS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	15/16 In 24 mm
Dimensions	H: 1.32 in (3.35 cm) x W: 0.94 in (2.39 cm)

1/2" female NPT adapter, S.S. QTHA-4FS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	1-1/8 In 29 mm
Dimensions	H: 1.66 in (4.22 cm) x W: 1.12 in (2.84 cm)

1/2" female NPT Quick-connect adapter, S.S. QTHA-4FS0-QD

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Teflon

1/2" female NPT Quick-connect adapter, S.S. QTHA-4FS0-QD

Dimensions	H: 1.69 in (4.29 cm) x W: 1.39 in (3.53 cm)
------------	---

1/4" tube adapter, S.S. QTHA-2TS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N
Dimensions	H: 1.47 in (3.73 cm) x W: 0.56 in (1.42 cm)

3/8" tube adapter, S.S. QTHA-3TS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Dimensions	H: 1.53 in (3.89 cm) x W: 0.72 in (1.83 cm)

1/2" tube adapter, S.S. QTHA-4TS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Dimensions	H: 1.7 in (4.32 cm) x W: 1 in (2.54 cm)

5/16-24 UNF DP Transmitter adapter, S.S. QTHA-FRS0

Compatible with	Rosemount 2051 Series DP Pressure Transmitters, Rosemount 3051 Series DP Pressure Transmitters, Yokogawa EJ series DP Pressure Transmitters, Anderson Greenwood M25 Block and Bleed Valves, Anderson Greenwood M251 Block and Bleed Valves, Foxboro (by Schneider Electric) IDP10, Foxboro (by Schneider Electric) IDP15, Foxboro (by Schneider Electric) IDP31, Foxboro (by Schneider Electric) IDP32, Foxboro (by Schneider Electric) IMV25
Country of origin	USA

5/16-24 UNF DP Transmitter adapter, S.S. QTHA-FRS0

Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Dimensions	H: 2.16 in (5.49 cm) x W: 0.56 in (1.42 cm)

1/4-28 UNF DP Transmitter adapter, S.S. QTHA-HNS0

Compatible with	Honeywell Smartline ST700 Pressure Transmitter, Honeywell Smartline ST800 Pressure Transmitter
Country of origin	USA
Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Dimensions	H: 2.02 in (5.13 cm) x W: 0.56 in (1.42 cm)

Quick-test tee, S.S. QTHA-HSTS

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Dimensions	H: 1.96 in (4.98 cm) x W: 1.25 in (3.18 cm)

Male Quick-test union, S.S. QTHA-HHSU

Country of origin	USA
Has Check Valve	No

Male Quick-test union, S.S. QTHA-HHSU

Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Dimensions	H: 1.25 in (3.18 cm) x W: 0.56 in (1.42 cm)

Quick-test hose, S.S. ends, 6ft long QSQS-HOS-6ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Inner Diameter	0.08 In / 3.00 mm
Length	6 ft / 2.00 m
Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT

Quick-test hose, S.S. ends, 3ft long QSQS-HOS-3ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Inner Diameter	0.08 In / 3.00 mm
Length	3 ft / 92 cm
Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	0.00 InHg / 0.0 kPa

Quick-test hose, S.S. ends, 3ft long QSQS-HOS-3ft

Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT