

Part No.

QTHP-5KPSIG-D

5kpsi / 35 MPa Hydraulic hand pump, 5,000 psi digital pressure gauge

5kpsi / 35 MPa Hydraulic hand pump, 5,000 psi digital pressure gauge



QTHP-5KPSIG-D

Included Items

- Hand Pump - QTHP 5000 psi / 35 MPa Hydraulic Pump (QTHP)
- Pressure Reference - LC10 pressure gauge, 5000 psi / 350 bar / 35 MPa, 1/4" Male NPT bottom connection (LC10-GT2M)
- Reference Connection - 1/4" female NPT x female Quick-test, no check-valve, brass (QTHA-2FBA)
- Process Connection - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Hose - Quick-test 6900 psi hose, brass hose ends, 3 ft (92 cm) long (QTQT-HOS-3ft)

Specs/Attributes

Pressure Reference	Digital pressure gauge, 5000 PSIG Pressure
Hose 1	Quick-test Hose, Stainless Steel ends, 3ft / 0.9m long
Reference Connection	1/4" Female NPT
Country of origin	USA

Specs/Attributes

Weight	52 oz / 3.25 lbs / 1.47 kg
Dimensions	H: 5.7 in (14.48 cm) x W: 6 in (15.24 cm) x D: 8.6 in (21.84 cm)

Hand Pump QTHP

Outlet Port	Male Quick-test, Male Quick-test with cap and chain
Pressure Media	Liquid
Materials	Anodized Aluminum, Brass, Stainless Steel, Polysulfone
Max Pressure	5000 PSI / 345 bar / 35 MPa
Media Compatibility	Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Mineral Oil, Petroleum Based Oil, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil
Seal Materials	Buna-N, Teflon
Fine Adjustment Resolution	0.01 PSI / 0.07 mbar / 0.07 kPa
Min Temperature	-29 °F / -34 °C
Country of origin	USA
Max Temperature	140 °F / 60 °C
Weight	46.9 oz / 2.93 lbs / 1.33 kg
Dimensions	H: 5.7 in (14.48 cm) x W: 6 in (15.24 cm) x D: 10.6 in (26.92 cm)

Pressure Reference LC10-GT2M

Battery Count	2
Battery Life	1500 Hours
Battery Type	AA Alkaline (LR6)
Burst Pressure	20000 PSI / 1380 bar / 140 MPa
Certifications	Certified to CSA Standard C22.2 No. 61010-1, Conforms to UL / IEC / EN / AS Standard No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU
Country of origin	USA
Electrical Rating	50 mA @ 5 VDC
Engineering Units	atm, bar, kPa, MPa, psi, inHg @39°F, kgf / cm ² , ftH ₂ O @39°F, cmHg @ 0°C, oz / sqin
Ingress Protection	IP67 (1 meter water submersion for 30 minutes)
LCD Display	2.4 in / 61 mm segmented LCD Display
Materials	ABS / Polycarbonate Blend, Powder Coated Aluminum
Max Pressure	5000 PSI / 345 bar / 35 MPa
Max Storage Temperature	165 °F / 75 °C
Max Temperature	120 °F / 50 °C
Measurement Type	Gauge Pressure
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Storage Temperature	-40 °F / -40 °C
Min Temperature	-4 °F / -20 °C
Operating Altitude (max)	10,000 ft (3050 m)

Pressure Reference LC10-GT2M

Pressure Measurement Uncertainty	+/- 0.25% of Full Scale (ASME Grade 3A/ISO Class 0.25)
Process Connection	1/4" Male NPT
Protection Class	Pollution Degree 2 (UL / IEC 61010-1)
Relative Humidity	0% to 90% (-10 to 35 °C) , 0% to 70% (35 to 50 °C)
USB Connection	USB (Micro B)
Wetted Materials	316 Stainless Steel
Wrench Size	23 mm 7/8 In
Weight	12.6 oz / 355 grams
Dimensions	H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 4.1 in (10.41 cm)

Reference Connection QTHA-2FBA

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Pressure	5000 PSI / 345 bar / 35 MPa
Max Temperature	225 °F / 105 °C
Max Vacuum	0.00 In Hg / 0.00 mm Hg
Wrench Size	3/4 In 19 mm
Dimensions	H: 1.52 in (3.86 cm) x W: 0.75 in (1.91 cm)

Process Connection QTHA-2MB0

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Pressure	5000 PSI / 345 bar / 35 MPa
Max Temperature	225 °F / 105 °C
Max Vacuum	0.00 In Hg / 0.00 mm Hg
Min Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm)

Hose QTQT-HOS-3ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Inner Diameter	0.08 In / 3.00 mm

Hose QTQT-HOS-3ft

Length	3 ft / 92 cm
Materials	Brass
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Temperature	140 °F / 60 °C
Max Vacuum	0.00 In Hg / 0.00 mm Hg
Min Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT