

Part No.

QTQT-HOS-50ft

Quick-test hose, brass hose ends, 50 ft (15.2 m) long (with hose reel)

Hoses that provide a very quick, low volume, high pressure way of connecting to any pressure instrumentation, hand pump, calibration source or device under test

Features

- Low volume reduces the pumping effort or compressed gas usage in pressure calibration
- No thread sealant required – connect adapters to without wrenches, thread sealant or thread tape
- Bubble tight connections to 6900 psi (475 bar) with no moving parts
- No moving parts reduces maintenance to almost zero
- Hose is hard to break and very flexible
- Adapt from hose to virtually any device under test with only one connection
- Silver color dramatically reduces the effect that changing temperature has on pressure stability
- A strain-relief on each hose end reduces wear and dramatically increases hose life
- Made in U.S.A.



QTQT-HOS-50ft



99 Washington Street
Melrose, MA 02176
Phone 781-665-1400
Toll Free 1-800-517-8431

[Visit us at www.TestEquipmentDepot.com](http://www.TestEquipmentDepot.com)

Specifications

| | |
|---------------------|---|
| Length | 50 ft |
| Pressure Range | 0 to 6900 psi (0 to 475 bar) |
| Burst Pressure | 27000 psi (1,860 bar) |
| End 1 | Female Quick-test, brass |
| End 2 | Female Quick-test, brass |
| Temperature range | -40 to 140 °F (-40 to 60 °C) |
| Outer Diameter | 0.2 in (5.1 mm) |
| Inner Diameter | 0.08 in (2.0 mm) |
| Minimum Bend Radius | 1 in (25.4 mm) |
| Color | Silver |
| Construction | Polyamide core tube, High tensile synthetic fiber and polyamide outer cover |
| End materials | Brass |
| Fluid Media | Water, Petroleum Based Oil, Air, Inert Gas |