

Part No.

# QTHA-KIT38

*Premium Transmitter Test Hose Kit*

Kit containing 1/8" MNPT, 1/4" MNPT Quick-test fittings, 1/4" MBSP adapter, 1/4" MNPT Quick-connect, 3ft hose, tape, bag



QTHA-KIT38

## Included Items

- Reference Connection (Qty 2) - 1/8" male NPT x male Quick-test, no check-valve, with cap and chain, brass (QTFT-1MB0)
- Reference Connection (Qty 2) - 1/4" male NPT x male Quick-test, no check-valve, with cap and chain, brass (QTFT-2MB0)
- Reference Connection - G 1/4" male BSPP (ISO 228/1) x male Quick-test, no check-valve, brass (QTHA-2MB0-RS)
- Bonded Seal - 1/4" male RS bonded seal ring, steel and Buna-N (QTHA-2BR-RS)
- Reference Connection - 1/4" male NPT QD (Quick-connect) Adapter, S.S. (QTHA-2MS0-QD)
- Hose - Quick-test 6900 psi hose, brass hose ends, 3 ft (92 cm) long (QTQT-HOS-3ft)
- Thread Sealant - PTFE sealing tape, 0.5 inches wide, 10,000 psi, UL Listed (SM-0090)
- Bag - Zippered bag to hold hose and adapters, nylon (SM-0084)

## Specs/Attributes

Weight	12.21 oz / 345 grams
Dimensions	H: 6.5 in (16.51 cm) x W: 6.5 in (16.51 cm) x D: 1 in (2.54 cm)

## Reference Connection (Qty 2) QTFT-2MB0

Country of origin	USA
Has Cap and Chain	Yes
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test

## Reference Connection (Qty 2) QTFT-2MB0

Weight	1.95 oz / 55 grams
Dimensions	H: 1.85 in (4.7 cm) x W: 0.71 in (1.8 cm) x D: 0.71 in (1.8 cm)

## Reference Connection QTHA-2MS0-QD

Burst Pressure	20000 PSI / 1380 bar / 140 MPa
Country of origin	USA
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Seal Materials	Buna-N, Teflon
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Weight	3.55 oz / 100 grams
Dimensions	H: 1.88 in (4.78 cm) x W: 1 in (2.54 cm) x D: 1 in (2.54 cm)

## Bonded Seal QTHA-2BR-RS

Max Pressure	0.00 PSI / 0.00 mbar / 0.00 kPa
Max Vacuum	0.00 InHg / 0.0 kPa
Materials	Plated Steel
Seal Materials	Buna-N
Country of origin	USA
Weight	0.08 oz / 2.27 grams
Dimensions	H: 0.81 in (2.06 cm) x W: 0.09 in (0.23 cm) x D: 0.09 in (0.23 cm)

## Hose QTQT-HOS-3ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	3ft / 0.91 m
Inner Diameter	0.08 In / 3.00 mm
Length	3 ft / 92 cm
Materials	Brass
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm

**Hose** QTQT-HOS-3ft

Outer Diameter	0.20 In / 6.00 mm
Type	QT
Weight	2.68 oz / 76 grams

**Bag** SM-0084

Materials	Zippered Nylon
Country of origin	USA
Weight	3 oz / 85 grams
Dimensions	H: 6.5 in (16.51 cm) x W: 6.5 in (16.51 cm) x D: 0.5 in (1.27 cm)