

RIDGID Tool (Utility)



Cut wire, crimp connectors and punch boxes with just one tool via the patented RIDGID[®] QuickChange System[™].

- Interchangeable heads allow for tool customization to meet individual needs
- Inline design for easy, one-handed operation, even in tight spots
- 360° head rotation increases accessibility in difficult to maneuver spaces
- Bright white LED light provides direct illumination of your work
- · Built-in sensors and LED indicators ensure tool performance, monitor battery life and indicate when the tool requires service
- Industry-leading service interval maximizes uptime on the job site
- Rubber overmolded grips for superior comfort and control
- Automatic ram retraction when cutting and crimping •
- Nylon straps allow easy tethering or hoisting



Test Equipment Depot - 800.517.8431 99 Washington Street, Melrose, MA 02176 TestEquipmentDepot.com

THE RIDGID® RE 6 FULLY CUSTOMIZABLE TO MEET YOUR NEEDS.



Test Equipment 99 Washington Street **Depot** Melrose, MA 02176 Phone 781-665-1400 Toll Free 1-800-517-8431

Visit us at www.TestEquipmentDepot.com

CRIMPING HEADS Select from 4 different crimping heads.





UC-60 BG

BG and D3 Grooves





6-TON DIES

• Dies clearly marked with color codes to easily match with proper lug

• Fully closing hex crimp profile

	COPPE	R DIES	
CATALOG NO.	DESCRIPTION		
53548	6T Copper Round Die Se	et	
	Individual dies that co	me in set listed bel	OW.
CATALOG NO.	DESCRIPTION	CATALOG NO.	DESCRIPTION
53628	DIE, 6T RD CU 600	53588	DIE, 6T RD CU 2/0
53623	DIE, 6T RD CU 500	53583	DIE, 6T RD CU 1/0
53618	DIE, 6T RD CU 400	53578	DIE, 6T RD CU #1
53613	DIE, 6T RD CU 350	53573	DIE, 6T RD CU #2
53608	DIE, 6T RD CU 300	53568	DIE, 6T RD CU #4
53603	DIE, 6T RD CU 250	53563	DIE, 6T RD CU #6
53598	DIE, 6T RD CU 4/0	53558	DIE, 6T RD CU #8
53593	DIE, 6T RD CU 3/0		

START WITH THE BASE KIT.

Includes RE 6 Tool, two batteries, charger and carrying case.



SPECIFICATIONS

- 6-ton hydraulic force output • Approximate cycle time: 5 seconds

- Temperature limit: 15°F 122°F (10°C 50°C)

CATALOG	DESCRIPTION	WEI	GHT
NO.		(lb.)	(kg)
52088	RE 6 Electrical Tool Kit (No Heads)	20.8	9,4

ORDER THE HEADS YOU NEED FOR THE WORK YOU DO.

CUTTING HEADS Select from two different cutting heads.



CU/AL SCISSOR CUTTER HEAD

• Designed for cutting up to 750 kcmil (MCM) copper/aluminum building wire and 500 kcmil (MCM) copper fine stranded wire

CATALOG NO.	DESCRIPTION	WEI (lb.)	GHT (kg)
47918	SC-60C Cutter Head with Copper/Aluminum Wire Blades	4.75	2,15
47923	Replacement Blades for Copper/Aluminum Wire	0.5	0,23

PUNCHING HEAD





ACSR CUTTER HEAD

• Designed for cutting up to 477 kcmil (MCM) ACSR

CATALOG NO.	DESCRIPTION	WEI (lb.)	GHT (kg)
49408	SC-60C Cutter Head with ACSR Blades	4.75	2,15
47928	Replacement Blades for ACSR	0.5	0,23

SWIV-L-PUNCH[™] KNOCKOUT PUNCH HEAD

- Punches up to 4" holes in 12 gauge mild steel and 14 gauge stainless steel
- Compatible with knockout punch dies from RIDGID and other manufacturers (sold separately)

CATALOG NO.	DESCRIPTION		GHT (kg)
59418	Swiv-L-Punch Knockout Punch Head and Accessories (DrawBolts, Spacers, Thread Adapter & Step Drill Bit)	6	2,7



• Service interval: 32,000 cycles

• Power: RIDGID[®] 18V Advanced Lithium Battery platform



4PIN[™] DIELESS CRIMP HEAD

 Classified to UL 1976 for copper connectors and wire from #8AWG to 750 kcmil (MCM) and aluminum connectors and wire from #8AWG to 500 kcmil (MCM)

CATALOG	DESCRIPTION	WEI	IGHT
NO.		(lb.)	(kg)
52283	4P-6 4PIN Dieless Crimp Head Only	5.8	2,6



For use With:

- Copper Taps#10 Solid – 2/0 Stranded
- AL and ACSR Taps #14 Solid 4/0 ACSR
- ...#6 4/0 ACSR • Stirrups
- Tension Splices #10 Stranded – 4/0 ACSR
- Lugs & Splices #8-350 MCM AL, 500 MCM CU
- Services Entrances #10 Stranded 4/0 ACSR

O and D3 Grooves

ATALOG		WEIGHT	
NO.	DESCRIPTION	(lb.)	(kg)
56793	UC-60 BG, D3/W-Die Crimp Head	4.85	2,20
6798	UC-60 O, D3/W-Die Crimp Head	4.85	2,20
		NO. DESCRIPTION 56793 UC-60 BG, D3/W-Die Crimp Head	NO. DESCRIPTION (lb.) 56793 UC-60 BG, D3/W-Die Crimp Head 4.85

LR-60B LATCHING ROUND CRIMP HEAD

- Classified to UL 1976 for copper connectors and wire from #8AWG to 600 Kcmil and aluminum connectors and wire from #8AWG to 350 Kcmil
- Compatible with 6-ton dies from RIDGID and other manufacturers.
- LR-60B designed for 6-ton U Dies ONLY

CATALOG	DESCRIPTION	WEI	GHT
NO.		(lb.)	(kg)
47753	Latching Round Crimp Head Only**	5.3	2,4

*For the most up to date RIDGID Crimp Die/Electrical Connector Compatibility Charts, go to www.RIDGID.com/CrimpDies

**Crimp dies sold separately

CATALOG NO.

53553

CATALOG NO.

53688

53683

53678 53673

53668

53663





NOW USING ST			
ALUMINU	JM DIES		
DESCRIPTION			
6T Aluminum Round Die	Set		
Individual dies that cor	ne in set listed below.		
DESCRIPTION	CATALOG NO		

53658

53653 53648

53643

53638

53633

DIE, 6T RD AL 350

DIE. 6T RD AL 4/0

DIE, 6T RD AL 2/0

DESCRIPTION

DIE, 6T RD AL 1/0

DIF 6T RD AI #4

DIE, 6T RD AL #6



RE 6 ACCESSORIES

CATALOG NO.	DESCRIPTION		GHT (kg)
46818	RE 6 Tool Only	6.4	2,9
52083	RE 6 Tool Case Only	9.45	4,3
44693	18V Advanced Lithium 2.0Ah Battery	1.0	0,5
44698	18V Advanced Lithium 4.0Ah Battery	1.5	0,7
43458	Advanced Lithium Battery Charger	1.8	0,8
44798	Advanced Lithium Battery Charger Replacement Cord	0.3	0,1







Visit us at www.TestEquipmentDepot.com