



# SF40A

Impact Printer

Test Equipment Depot - 800.517.8431 - TestEquipmentDepot.com



## *OHAUS Value in a Full-Featured, Portable Printer*

The SF40A combines high performance and multiple functions to offer OHAUS quality and durability in a portable printer. The SF40A offers advanced functionality in an easy-to-use and set up printer at an exceptional value. This versatile printer is ideal for use in conjunction with OHAUS balances and scales in laboratory, industrial, and educational applications to ensure accurate documentation of weighing results.

### *Unique Features:*

- The statistics and totalization modes and real time clock complement OHAUS weighing instruments' application modes and offer functionality that assists the reporting processes.
- SF40A helps support the efficiency of the weighing and recording processes. RS232 interface and PC configuration software make setting up and using the printer fast and simple.
- With the ability to print in 13 different languages, SF40A can print in the language of the connected device to support universal operation.

# SF40A Impact Printer

Model	SF40A
Number of Columns	40 columns
Print Speed	Approximately 1.2 lines per second
Application Modes	Totalization, Statistics (Statistics printout includes number of samples, average value, standard deviation, minimum, maximum, min-max differential, and total sample weight sum)
Paper Roll (W x Dia.)	Standard paper 2.26 in. x Ø 2.36 in. max / 57.5 mm x Ø 60 mm max.
Power Requirements	AC adapter Input: 100 – 240 VAC, 50 - 60 Hz AC adapter output: 12 VDC, 2.5 A
Interface	RS232C
Ambient Temperature	32 °F – 104 °F / 0 °C – 40 °C
Printer Dimensions (W x L x H)	5.5 x 8.1 x 2.9 in. / 140 x 205 x 75 mm
Net Weight	1.6 lb / 740 g (Paper roll included)
Shipping Weight	1.8 lb. / 0.8 kg

## Other Standard Features and Equipment

Status indicator, 40 characters per line, perform zero and tare operations directly from the printer. Full functionality with Discovery, Adventurer™ Pro, Explorer®, Navigator®, MB Series Moisture Analyzers and 'T' Series indicators. Statistics and Totalization not supported on CKW Bench Scale and Scout® Pro Series.

Multi-Language Printing: English, Spanish, German, Italian, French, Chinese, Korean, Japanese, Russian, Polish, Portuguese, Hungarian and Czech.

## Accessories

Paper (Included) .....	12120799
Paper Rotary Axis (Included).....	30063920
Ink Ribbon (Included).....	30529322
Printer Cable for Explorer, Adventurer, Pioneer, MB 45/35/25/23, Ranger, Trooper, Valor 7000, "T" Series dry-use "P" indicators & associated	
Defender bench scales (Included) .....	30529323
Cable Adapter (Included) .....	30059316
Printer Cable for CKW and "T" Indicators (Not Included).....	80500552
Power Cable AU, SF40A (Not Included) .....	12120313

## Compliance

- **Product Safety:** IEC/EN 61010-1
- **Electromagnetic Compatibility:** IEC/EN 61326-1 Class B, Basic environments; FCC Part 15 Class A; Canada ICES-003 Class A
- **Compliance Marks:** CE, RCM, UKCA, CSA
- **Other:** WEEE, RoHS

## Outline Dimensions

