

Product Specifications

PROVEN DATA LOGGING SOLUTIONS



ACR SmartButton Temperature Data Logger

The ACR SmartButton is a miniature-sized temperature logger that is extremely low-cost and easy to use. Because of its small size and low-cost, you can purchase tens or hundreds of them for multiple-site temperature monitoring. To get you started, purchase the SmartButton Starter Pack. It includes one SmartButton, Interface cable, and TrendReader for SmartButton Software. So simple and easy to use, anyone can start data logging today!

APPLICATIONS

Food processing verification, pharmaceutical storage, laboratories, transportation of temperature sensitive goods, equipment run time, HVAC system testing and balancing, etc.

GENERAL SPECIFICATIONS

17.35mm diameter x 5.89mm height (0.68" x 0.23") Size:

4 grams (0.14 ounces) Weight:

Case Material: Stainless Steel

3.0 volt Lithium - Approximate 10 year battery life using 20 min Battery:

sample rate at 15°C (*See product lifetime table for more information)

Resolution: 8-bit (1 part in 256)

User selectable (magnetic backing, plastic Mounting

hard plastic or self-adhesive backing material)

Clock Accuracy ±2 minutes per month from 0° to 45°C (32° to 113°F)

Continuous (First-in, First-out) or Stop When Full (Fill-then-stop) Sampling Methods:

Operating Limits: -40°C to 85°C (-40°F to 185°F)

PC Requirements: Windows PC with at least one free USB Port Software Requirements: ACR TrendReader for SmartButton Software

(Compatible with Windows XP, Vista, 7, 8 [32 bit and 64 bit] and 10)

Communication: USB/ACR SmartButton Interface

TEMPERATURE SENSOR SPECIFICATIONS

Type: Silicon

Range: -40°C to 85°C (-40°F to 185°F)

±1.0°C from -30°C to 45°C (± 1.8°F from -22°F to 113°F) Accuracy:

±1.5°C from 45.5°C to 85°C (± 2.7°F from 114°F to 185°F)

ORDERING INFORMATION

Cat#: SmartButton USB Starter Pack* 01-0182 SmartButton (Single) 01-0180

*Starter Pack includes: One SmartButton Data Logger TrendReader for SmartButton Software CD USB interface Cable, Magnetic Backing, Plastic ID Tag, Adhesive Backing Quick Start Guide

















MINIMUM PRODUCT LIFETIME vs SAMPLE RATE AT DIFFERENT TEMPERATURES



SPECIAL FEATURES

- ACR SmartButton measures temperature in 0.5°C increments
- Logs up to 2048 consecutive temperature measurements in internal memory
- Programmable temperature-high and temperature-low alarm trip points
- Records up to 24 time stamps and durations when temperature leaves the range specified by the trip points (12 periods for too hot and 12 for too cold)
- Automatically wakes up and measures temperature at user-programmable intervals from 1 to 255 minutes
- Unique, factory-lasered and tested 64-bit registration number (8-bit family code + 48- bit serial number + 8-bit CRC tester) assures absolute traceability because no two parts are alike

- Chip-based data carrier compactly stores information
- SmartButton can be accessed while affixed to an object



All dimensions shown are in millimeters



