

Snap and Pres-N-Snap Tool

Snap s are used to connect a ground cord to a static mat. Grommet and Clinch Style snaps are attached with a Pres-N-Snap. Nickel plated brass snaps provide electrical connection and a long service life.



SNAPSOCKET3/8:

- 3/8" (10 mm) Female Snap Grommet Style

Socket snaps are held in place by crimping the tip of an eyelet though the center of the socket with a snap tool. This traps the mat between the socket on the top of the mat and the eyelet on the back of the mat. 10 sockets and eyelets are included in each pack.



SNAPSOCKET3/8

Item	Description
SNAPSOCKET3/8	3/8" Female Socket
3033	3/8" Male Stud and Eyelet
PRES-N-SNAP TOOL	Snap Attaching Tool

3033:

- Male Snap Fastener 0.125" Hole

Stud snaps are held in place by crimping the tip of an eyelet though the center of the stud with a snap tool. This traps the mat between the stud on the top of the mat and the eyelet on the back of the mat. 10 studs and eyelets are included in each pack.



3033




PRES-N-SNAP TOOL:

- For attaching Grommet Style snaps
- Versatile and easy to use
- Capable of setting numerous brands of fasteners simply by changing the dies

Pres-N-Snap Tool Instructions

1.


MAT



EYELET

2.

SOCKET OR STUD



1. Press the eyelet through the mat from the back. (A utility knife or phillips screw driver can be used to make a hole.)

2. Place the socket or stud on top of the eyelet

Test Equipment Depot - 800.517.8431 - 99 Washington Street Melrose, MA 02176

TestEquipmentDepot.com

SNAPS AND PRES-N-SNAP TOOL

SCS

Specifications and procedures subject to change without notice.

**DRAWING
NUMBER**
PRES-N-SNAP

DATE
July
2017