

SINGLE STICK DIGITAL VOLTMETER

SVM-25



The single stick digital voltmeter, model SVM-25, is a highly accurate one stick voltmeter with a large digital display, peak hold and capacitive test point mode.

The SVM-25 measures voltage up to 25kV and can be used in both underground and overhead applications. The large, bright digital display is ideal for reading measurements at farther distances or in bright sunlight, while the housing makes it an incredibly rugged and durable voltmeter.

For highly accurate voltage measurements on an incredibly easy to read screen, the SVM-25 is a convenient solution.



**Test Equipment
Depot**
1-800-517-8431

99 Washington Street
Melrose, MA 02176
Phone 781-665-1400
Toll Free 1-800-517-8431



Visit us at www.TestEquipmentDepot.com

SINGLE STICK DIGITAL VOLTMETER SVM-25

Features

- 1 Over-sized, digital LED display
- 2 One button operation for test modes
 - Line-to-ground measurements
 - Test point measurements
 - Peak hold
- 3 Ultra-light, high-strength molded housing
- 4 Dual hotstick connection options (universal spline and shotgun stick)
- 5 Heavy duty insulated ground cord, extends up to 12 feet



ORDERING INFORMATION

SVM-25	Includes 1 piece each of: Voltmeter (SVM-25) Overhead Hook Brass Probe (025-OLPS-5) Plastic Carrying Case for Voltmeter and Accessories (CS-SVM)
SVM-25/K01	Includes 1 piece each of: Voltmeter (SVM-25) Overhead Hook Brass Probe (025-OLPS-5) Proof Tester® Voltmeter Tester (PT-5000B) Plastic Carrying Case for Voltmeter and Accessories (CS-SVM)
SVM-25/K02	Includes 1 piece each of: Voltmeter (SVM-25) Overhead Hook Brass Probe (025-OLPS-5) Underground Adapter Bushing Probe, 15kV & 25kV Class (ASP-15/25) Proof Tester® Voltmeter Tester (PT-5000B) Plastic Carrying Case for Voltmeter and Accessories (CS-SVM)
025-OLPS-5	Overhead Hook Brass Probe
025-OLPS-6	Overhead Pigtail Brass Probe
PT-5000B	Proof Tester® Voltmeter Tester - Tests Voltmeter Prior to Use
GCP-1	General Purpose Insulated Probe
ASP-15/25	Underground Adapter Bushing Probe, 15kV & 25kV Class
EA-15/25	Loadbreak Elbow Adapter, 15kV & 25kV Class
CS-SVM	Plastic Carrying Case for SVM-25 and Kits
S-4H	4' Fixed Length Fiberglass Hotstick
S-6H	6' Fixed Length Fiberglass Hotstick

SPECIFICATIONS

MODEL NUMBER	SVM-25
OPERATING VOLTAGE RANGE	5V to 25kV line-to-ground
OPERATING FREQUENCY	25-1000Hz
ACCURACY	Within 1% of reading +/- 3 counts
LED NUMERAL HEIGHT	0.7", indicates 3 digits
BATTERY	9V lithium or alkaline
BATTERY LIFE	8 hours continuous use under normal operating conditions
OPERATING TEMPERATURE RANGE	-20°F to +120°F (-29°C to +49°C)
WEIGHT (WITHOUT PROBES)	2.25 lbs (1.02kg)
DIMENSIONS (WITHOUT PROBES)	14" L x 4.6" W x 4.1" H (36cm x 12cm x 10cm)
CORD LENGTH	Retracted: 3.5' (1.7m) Extended: 12' (3.6m)

All sales are subject to the terms and conditions of the Limited Warranty and Limitation of Liability set forth in the product Instruction Manual and at www.HDElectricCompany.com. Users must read and agree to the Limitation terms, as stated, before using the product. HD Electric Company is committed to ongoing review and improvement of its product lines, and thus reserves the right to modify product design and specifications without notice. HD Electric Company® products are available through HDE® sales representatives worldwide. Printed in U.S.A. © HD Electric Company 2019 • Bulletin No. SVM-200a