

99 Washington Street Melrose, MA 02176 Phone 781-665-1400 Toll Free 1-800-517-8431

Visit us at www.TestEquipmentDepot.com

TA33

Temperature Alarm with Display & Battery Backup

Set your temperature threshold and the TA33 provides reliable protection for your temperature sensitive areas. The battery backup allows continuous monitoring even during power outages. The easy to read display shows current Temperature, Alarm Status, Over/ Under mode indicator and Alarm Set Point and Temperature.

Features/Benefits

- Adjustable range from -40°F to +160°F (-40°C to +71°C)
- Back Lit Display
- 90 db audible alarm
- · Adjustable alarm temperature ranges
- Built-in terminals for remote alarm or telephone dialer connection
- Switch for 'No delay' or '1 hour delay'

Applications

- Food Markets, Convenience Stores, Supermarkets
- Restaurants
- Florists, Greenhouses
- Laboratories, Phamaceutical Storage Facilities
- Refrigerated Transport, Cold Storage Facilities
- Computer Rooms





Specifications

-40°F to 160°F (-40° to 71°C)
+/- 2°F (+/- 1°C)
1
Precision Thermistor with 6 ft. cable (21301)
Thermistor
200 ft,
-10°F to +130°F (-23°C to +54°C)
Screw type,120VAC, 10 Amps.
12 V Adapter 120 VAC with 6 ft. cable included
(220V available). 24 Hrs 9V Battery backup.
Hi-impact thermoplastic
Flat Surface, external holes provided
4.8" x 3.2" x 1.4" (12.2cm x 8.1cm x 3.6cm)
1 year

Accessories

21301	Probe
21387	10' Probe Extension
21392	50' Probe Extension
ADTA	Phone Dialer

ADTA

Auto Dialer For Temperature Alarms

- Call up to 4 telephone numbers
- Internal 9V back up battery (not included)
- 16 second message
- LCD display
- Non-Volatile memory for numbers and voice message
- 120V power adapter (included)

