



- Wire: PVC UL 1803 / 18AWG, length: 1100 ± 30mm, out diameter: 4.0mm, temperature tolerance range: -40°C ~ 105°C, braid copper wires: 170/0.08mm.
- Terminal: 105° angle 4mm brass banana plug (nickel plated) with caged and insulated sheathing to avoid the brass oxidation.
- Rating: EN 61010-031: 2002 + A1:2008 CAT III 1000V 10A/CAT IV 600V 10A.

**BST-TL01**

**BST-TL01**



- Wire: PVC UL 1803 / 18AWG, length: 1100 ± 30mm, out diameter: 4.0mm, temperature tolerance range: -40°C ~ 105°C, braid copper wires: 170/0.08mm.
- Terminal: 4mm with brass nickel plated.
- Rating: EN 61010-031: 2002 + A1:2008 CAT IV 1000V 10A.

**BST-TL04**

**BST-TL04**

- Stacking-shrouded plug each end.
- Silicone wire 50cm.
- Axial mount 4mm banana jack.
- BST-TL16R (Red), BST-TL16B (Black), BST-TL16G (Green).



**BST-TL16**

**BST-TL16**

- Stacking-shrouded plug.
- Axial mount 4mm banana jack.
- BST-TL16HR (Red), BST-TL16HB (Black), BST-TL16HG (Green).



**BST-TL16H**

**BST-TL16H**



- Wire: PVC UL 1803 / 18AWG, length: 1100 ± 30mm, out diameter: 3.50mm, temperature tolerance range: -40°C ~ 105°C, braid copper wires: 64/0.12mm.
- Terminal: Right angle 4mm brass (nickel plated) banana plug with caged and insulated sheathing to avoid the brass oxidation.
- Rating: EN 61010-031: 2002 + A1:2008 CAT III 1000V 10A/CAT IV 600V 10A.

**BST-TL07**

**BST-TL07**



- Wide grip alligator clips with integral finger guard, large 35mm high tension spring mouth.
- Double insulated silicone wire 1m.
- Safety straight input plug.
- Rating: EN 61010-031: 2002 + A1:2008 CAT III 1000V 10A.
- BST-TL10AR (Red), BST-TL10AB (Black), BST-TL10AG (Green), BST-TL10AL: 90° angle 4mm banana plug.

**BST-TL10A**

**BST-TL10A**

- Stacking-shrouded plug each end.
- PVC insulated wire 50cm (0.08 / 170).
- Axial mount 4mm banana jack.
- EN 61010-031: 2002 CAT III 600V 10A.
- Color: Red and Black each (set).



**BST-TL16S**

**BST-TL16S**

- Stacking-shrouded banana plug, each end on 1.2m long Silicone wire.
- BST-TL17R (Red), BST-TL17B (Black).



**BST-TL17**

**BST-TL17**



- Wide grip alligator clips with integral finger guard and large 35mm high tension spring mouth.
- PVC-insulated wire (Red-15m - Yellow-10m, Black-10m, Green-5m).
- Rating: EN 61010-031: 2002 + A1:2008, CAT III 600V 2A.
- BST-TL15R SPL (Red), BST-TL15Y SPL (Yellow), BST-TL15B SPL (Black), BST-TL15G SPL (Green).
- For 3-wire/4-wire earth resistance tester use.

**BST-TL15**

**BST-TL15**



**BST-TL15L**

- Wide grip alligator clips with integral finger guard and large 35mm high tension spring mouth.
- PVC-insulated wire (Red-30m, Yellow-20m, Green-5m).
- Right angle connectors.
- For 3-wire earth resistance tester use.

**BST-TL15L**

- Large test probe handle with shrouded 4mm brass caged banana plug tip.
- Super insulated silicone wire 2.7m.
- Safety straight input plug connect with extra green guard.
- Warning: Input: Max. AC 1000V, Output: Max. DC 10kV. 3W, only available for insulation tester.
- EN 61010-031: 2002 + A1:2008 CAT III 10kVdc 2mA.

**BST-TL19**

**BST-TL19**



- For earth tester (Four wires).
- Terminal: 4mm brass banana plug.
- Wire: PVC, out dimension: 3.5mm, braid copper wires: 0.127/65mm, length: Black-3m, Blue-20m, Red-36m, Green-50m.
- Auxiliary earth spikes: 45cm.
- For 4-wire earth resistance tester use.

**BST-TL23**

**BST-TL23**





- Terminal: 4mm banana plug.
- Wire: PVC UL 1803, length: 1100mm ± 30mm, braid copper wires (200 of 0.08mm), temperature tolerance range: -40°C ~105°C, color: Red and Black each (set).
- EN 61010-031:2002 + A1:2008 CAT III 600V 15A.

**BST-TL25**

**BST-TL25**



- Tip: 2-4 mmg.
- EN 61010-031:2002 + A1:2008 CAT IV 600V 15A / CAT III 1000V 15A.
- Red and Black each (set).
- Tip: 4mm stainless steel caged banana probe tip.
- Jack: nickel plated, 4mm banana jack.
- The probe tip could be used into non-screw crocodile clips.
- Probes can be used with 4mm jack test leads.

**BST-TL31-C4**

**BST-TL31-C4**



- Tip: 2mm.
- EN 61010-031:2002 + A1:2008 CAT IV 600V 15A / CAT III 1000V 15A.

**BST-TL31-C6**

**BST-TL31-C6**



- BST-TL34-1 For 2mm probe tip.
- BST-TL34-3 For 4mm banana plug.
- BST-TL34-5 For 2mm probe tip (only for exposed 4mm probe tip).
- EN 61010-031:2002 + A1:2008 CAT III 1kV 10A / CAT IV 600V 10A.

**BST-TL34**

**BST-TL34**




- For 4mm banana plug.

**BST-TL37**

**BST-TL37**



- For 4mm banana plug.
- Rating: EN 61010-031:2002 + A1:2008 CAT IV 1kV 20A.



**BST-TL38CA**

**BST-TL38CA**