Test Equipment Depot - 800.517.8431 - TestEquipmentDepot.com

# TITANMAX<sup>™</sup> Digital Manifold



## Technological Innovations Combined with the Most Comprehensive Apps... YJACK VIEW<sup>®</sup> and measureQuick<sup>®</sup>.

The YELLOW JACKET<sup>®</sup> TITANMAX<sup>™</sup> Digital Manifold provides the easiest path to system measurements. This 4-valve manifold provides fast and accurate measurements for refrigeration and A/C systems. The high resolution backlit touchscreen display erases the need for multifunction buttons and provides clear graphical and digital measurements. It also features internal data logging. Connect via Bluetooth<sup>®</sup> to the YJACK VIEW<sup>®</sup> App or measureQuick<sup>®</sup> App for further analysis.

TITANMAX<sup>™</sup> P/N 40881 includes TITAN<sup>®</sup> Temperature Clamps (2), Vacuum Sensor and USB-C Charging/Data Cable.



## **FEATURES & BENEFITS**

Measures high and low side pressures and temperatures

- Displays vapor and liquid saturation temperatures
- Calculates system superheat and subcooling
- On-board data logging; export to your computer with USB or to your phone via YJACK VIEW<sup>®</sup> App
- Compatible with measureQuick® App
- Pressure hold mode displays rate of change for vacuum and positive pressure measurements
- Wirelessly measure and display relative humidity, dry bulb, wet bulb and dew point temperature alongside system pressure and temperature measurements with YJACK DEW<sup>®</sup>
- High resolution, full color, backlit, 5" touchscreen display
  - Ultimate user interface information on major screens
  - · Adjustable timing for auto shut-off
  - Touchscreen never has to be calibrated
  - Digital and graphical pressure/temperature measurements
  - Choose from relevant refrigerant profiles stored including A2L – may designate 3 favorites
- Robust housing with ergonomic grip
  - 4-way TITAN® valve block
  - Integrated magnets for mounting on equipment cabinet may also be used to store TITAN<sup>®</sup> Temperature Clamps
  - Pivoting hook
  - Convenient connections for USB port, temperature clamps, and vacuum sensor
- External vacuum sensor with high and low alarms
  - Vacuum measurements, set targets and leak testing
- Larger temperature clamps (2) for up to 1-5/8" pipes
- Bluetooth<sup>®</sup> 5.2; range up to 1,000 feet
- Maximum working pressure 740 psia (51.0 bar)
- Multiple languages: French, Spanish, German and English
- · Re-chargeable battery with life indicator
  - Continuous use no backlight: 80 hours
  - Continuous use with full backlight: 4.5 hours
- US and INTL units (bar, psia, psig, kPa, MPa, kg/cm2)
- IP52 certified
- Two-year warranty







m(



#### **40880 INCLUDES:**

- Vacuum Sensor (P/N 67044)
- Set of four PLUS II<sup>™</sup> Hoses: (3) 60" RYB, 1/4" (P/N 21985); (1) 60", 3/8" Yellow Vacuum Hose 3/8" Straight x 3/8" 45° (P/N 18160)
- TITAN® Temperature Clamps (2) (P/N 40846)
- USB-C Charge & Data Cable (P/N 40847)
- Backpack multi-pocket (P/N 40845)



#### **40885 INCLUDES:**

- Vacuum Sensor (P/N 67044)
- Set of six PLUS II<sup>™</sup> Hoses: (3) 60" RYB, 1/4" Compact Ball Valve (P/N 29985); (1) 60", 3/8" Yellow Vacuum Hose 3/8" Straight x 3/8" 45° (P/N 18160); (2) Compact Ball Valve 1/4" x 5/16" (P/Ns 29425 and 29465)
- TITAN® Temperature Clamps (2) (P/N 40846)
- USB-C Charge & Data Cable (P/N 40847)
- Backpack multi-pocket (P/N 40845)



#### **40887 INCLUDES:**

- YJACK VAC® Vacuum Gauge (P/N 67066)
- Set of six PLUS II<sup>™</sup> Hoses: (3) 60" RYB, 1/4" Compact Ball Valve (P/N 29985); (1) 60", 3/8" Yellow Vacuum Hose 3/8" Straight x 3/8" 45° (P/N 18160); (2) Compact Ball Valve 1/4" x 5/16" (P/Ns 29425 and 29465)
- YJACK® Temperature Clamps (2) (P/N 67061)
- USB-C Charge & Data Cable (P/N 40847)
- Backpack multi-pocket (P/N 40845)

### **YJACK VIEW® APP FEATURES**

- Measure HVAC/R system pressure, • temperature, saturation temperature, superheat and subcooling
- Monitor system evacuation status
- Check indoor air comfort and system efficiency with psychrometric air calculations: Percent relative humidity, dry bulb, wet bulb and dew point temperature measurements
- Monitor status of all nearby YJACK® and • TITANMAX<sup>™</sup> and P51-870 TITAN<sup>®</sup> devices
- Customize data view for each measurement
- Freely switch between multiple simulta-neous sessions without loss of data
- Create highly customized datalogs to be • saved or emailed from your smart device
- All relevant refrigerant profiles found ۲ in the REFPROP database
- Available on iOS (version 10 or later) and Android (version 8 or later) smart devices









**Evacuation Screen** 

UPC #	Description
40881	TITANMAX <sup>™</sup> Manifold, Vacuum Sensor, TITAN <sup>®</sup> Temperature Clamps (2), USB-C Cord
BACKPACK KITS WITH PLUS II™ HOSES	
40880	TITANMAX <sup>™</sup> Manifold, Vacuum Sensor, TITAN <sup>®</sup> Temperature Clamps (2), USB-C Cord, Set of (4) PLUS II <sup>™</sup> Hoses: (3) 60" 1/4" RYB, (1) 60" 3/8" Yellow Vacuum Hose 3/8" Straight x 3/8" 45°, Backpack
40885	TITANMAX <sup>™</sup> Manifold, Vacuum Sensor, TITAN <sup>®</sup> Temperature Clamps (2), USB-C Cord, Set of (6) PLUS II <sup>™</sup> Hoses: (3) 60" 1/4" RYB, Compact Ball Valve, (1) 60" 3/8" Yellow Vacuum Hose 3/8" Straight x 3/8" 45°, (2) Compact Ball Valve 1/4" x 5/16", Backpack
40887	TITANMAX <sup>™</sup> Manifold, YJACK VAC <sup>®</sup> Vacuum Gauge, YJACK <sup>®</sup> Temperature Clamps (2), USB-C Cord, Set of (6) PLUS II <sup>™</sup> Hoses: (3) 60" 1/4" RYB, Compact Ball Valve, (1) 60" 3/8" Yellow Vacuum Hose 3/8" Straight x 3/8" 45°, (2) Compact Ball Valve 1/4" x 5/16", Backpack

#### Test Equipment Depot - 800.517.8431 - TestEquipmentDepot.com



P/T Screen

