



## HOBO® U20L-04 Data Logger

### Water Level (13 ft) Data Logger

The HOBO U20L-04 is a low-cost, research-grade water level data logger for continuously measuring water level and temperature in a wide range of underwater environments. It features 0.1% measurement accuracy, a polypropylene housing for use in both fresh and salt water, and a non-vented design for convenient and hassle-free deployment.

This data logger requires either the U-DTW-1 Waterproof Shuttle or the Base-U-4 Base Station for configuration and data offload, HOBOWare software (free download). NOTE: HOBOWare Pro is required when using the U-DTW-1 Waterproof Shuttle. See compatible items below.

#### Helpful Links:

[Barometric Pressure Compensation Assistant Demo](#)

[Multi-rate Sampling Demo](#)

#### Key Advantages:

- Self-contained non-vented design enables easy deployment
- Ideal for use in both fresh and saltwater environments, including wells, streams, lakes, wetlands, and tidal areas
- Depths up to 13 feet
- Durable ceramic pressure sensor withstands freezing
- HOBOWare Pro software provides easy conversion to accurate water level reading, fully compensated for barometric pressure (see demo), temperature, and water density

Note: A calibration certificate is not offered for this logger. If you require a NIST-traceable calibration certificate, please see the [U20-001-04](#) (freshwater) or [U20-001-04-Ti](#) (saltwater).



## HOBO U20L-04 Data Logger Specifications

### Pressure (Absolute) and Water Level Measurements U20L-04

<b>Operation Range</b>	0 to 145 kPa (0 to 21 psia); approximately 0 to 4 m (0 to 13 ft) of water depth at sea level, or 0 to 7 m (0 to 23 ft) of water at 3,000 m (10,000 ft) of altitude
<b>Factory Calibrated Range</b>	69 to 145 kPa (10 to 21 psia), 0° to 40°C (32° to 104°F)
<b>Burst Pressure</b>	310 kPa (45 psia) or 18 m (60 ft) depth
<b>Water Level Accuracy*</b>	Typical error: ±0.1% FS, 0.4 cm (0.013 ft) water Maximum error: ±0.2% FS, 0.8 cm (0.026 ft) water
<b>Raw Pressure Accuracy**</b>	±0.3% FS, 0.43 kPa (0.063 psi) maximum error
<b>Resolution</b>	<0.014 kPa (0.002 psi), 0.14 cm (0.005 ft) water
<b>Pressure Response Time (90%)***</b>	<1 second at a stable temperature; measurement accuracy also depends on temperature response time

### Temperature Measurements

<b>Operation Range</b>	-20° to 50°C (-4° to 122°F)
<b>Accuracy</b>	±0.44°C from 0° to 50°C (±0.79°F from 32° to 122°F), see Plot A in manual
<b>Resolution</b>	0.10°C at 25°C (0.18°F at 77°F), see Plot A in manual
<b>Response Time (90%)</b>	10 minutes in water (typical)
<b>Stability (Drift)</b>	0.1°C (0.18°F) per year

### Logger

<b>Real-time Clock</b>	±1 minute per month 0° to 50°C (32° to 122°F)
<b>Battery</b>	2/3 AA, 3.6 Volt lithium, factory-replaceable
<b>Battery Life (Typical Use)</b>	5 years with 1 minute or greater logging interval
<b>Memory (Non-volatile)</b>	64K bytes memory (approx. 21,700 pressure and temperature samples)
<b>Weight</b>	Approximately 154 g (5.43 oz) in air Approximately 53.9 g (1.9 oz) in fresh water
<b>Dimensions</b>	3.18 cm (1.25 inches) diameter, 15.24 cm (6.0 inches) length; mounting hole 6.3 mm (0.25 inches) diameter
<b>Wetted Materials</b>	Polypropylene housing and lanyard; Viton and Buna-N O-rings; ceramic sensor in acetyl end cap; stainless steel screws suitable for saltwater
<b>Logging Interval</b>	Fixed-rate or multiple logging intervals, with up to 8 user-defined logging intervals and durations; logging intervals from 1 second to 18 hours. Refer to the <i>HOBOware User's Guide</i> for details.
<b>Launch Modes</b>	Immediate start and delayed start
<b>Offload Modes</b>	Offload while logging; stop and offload
<b>Battery Indication</b>	Battery voltage can be viewed in status screen and optionally logged in datafile. Low battery indication in datafile.
<b>Environmental Rating:</b>	IP68



The CE Marking identifies this product as complying with all relevant directives in the European Union (EU).

\* Water Level Accuracy: With accurate reference water level measurement, known water density, accurate Barometric Compensation Assistant data, and a stable temperature environment.

\*\* Raw Pressure Accuracy: Absolute pressure sensor accuracy includes all sensor drift, temperature, and hysteresis-induced errors.

\*\*\* Changes in Temperature: Allow 20 minutes in water to achieve full temperature compensation of the pressure sensor. Maximum error due to rapid thermal changes is approximately 0.5%.

