

WAL026409

WaveLED-UV T105 Lq2 5D CLA NA

Old item no.:

EAN-nr: 7040670264091

Stock code: C



Wave LED UV is an illuminated magnifier designed for the inspection of conformal coatings as well as for the detailed inspection of welds, solder joints and other areas of stress concentration. No knobs to tighten, nothing to adjust - a flexible, self-balancing shade and hands-free neck assembly combined with 45" heavy-duty internal-spring parallel, three-pivot K-arm, allows the lamp head to be secured in any position. The fully-enclosed neck design is ideal for environments where FOD is a concern. An automatic shut-off feature and step dimming further ensures energy savings. WAVE LED offers shadow-free 5-diopter (2.25X) magnification with light coming from both sides, as well as three-dimensional magnification lighting from the left or right. The 3D-feature is especially welcome when working with circuit board and similar delicate objects. Edge clamp mount. Color: light grey.



(For illustrative purpose only)



Lightsource	
Number of lamps	2
Lightsource	LED
Lamp power (W)	12
Lumen/Watt	59
LLMF LED 50000h Ta25	0.80
Average useful life (IEC 62717) Ta25	20000
Lumen Out	764
Optic	
Primary Lens (D)	5
Working distance (mm)	200
Magnification (X)	2.25
Technical data	
Maximum ambient temperature (°C)	25
IP classification	20

Electrical data	
Maximum voltage (V)	240
Maximum frequency (Hz)	60
Minimum frequency (Hz)	50
Voltage from (V)	110
Total consumption (W)	13
Termination	
Plug type	NA
Cord length (ft)	5
Mounting	Edge clamp
Dimensions	
Net weight (kg)	4,5
Arm length (in.)	45
Body	
Body color	Grey

Test Equipment Depot - 800.517.8431 - 99 Washington Street Melrose, MA 02176

TestEquipmentDepot.com

WAL026409

Drawings

