

Water Pump Pliers




- Right angle, laser heat-treated teeth provide long life and better grip
- Undercut tongue and groove won't slip
- Reinforcing edge minimizing stress breakage

SPECIFICATIONS							
	P4WP	P6WP	P8WP	P10WP	P12WP	P16WP	P20WP
Overall Length	4.50"	6.50"	8.00"	9.50"	12.00"	16.50"	20.25"
Jaw Length	.33"	.81"	1.12"	1.12"	1.50"	2.56"	3.00"
Joint Thickness	.13"	.47"	.40"	.47"	.50"	.59"	.59"
Handle Span	1.26"	1.69"	1.57"	1.57"	1.81"	1.93"	3.31"
Weight	.25 lbs	.55 lbs	1 lbs	1.2 lbs	1.8 lbs	3.5 lbs	4 lbs
# of Adjustments	3	5	4	5	7	8	12
Jaw Capacity	.50"	.87"	1.50"	1.50"	2.25"	4.25"	5.50"

Cementex double-insulated tools:

- Comply with the IEC 60900 standard
- Comply with ASTM F1505 standard
- Help you meet requirements of:
OSHA 1910.331-335 | NFPA 70E | CSA-Z462

Cementex double-insulated tools are:

- Tested to 10,000 VAC and rated for 1,000 VAC when working on live parts
- Made in the U.S.A.
- Marked with the international safety symbol— 

Cementex

The Safety Tool Specialists