



**DIGI-SENSE™**  
THE STANDARD IN PRECISION MEASUREMENT

## Digi-Sense™ Temperature/ Humidity Touch-Screen Recorder

**Virtually unlimited data logging with  
8GB of on-board memory**

Accurately measure and log temperature, relative humidity, and dew point conditions with this tablet-based instrument. An intuitive touch-screen display makes this recorder easy to use and view. Measured values are simultaneously displayed both graphically and digitally on a high-resolution, color display. Simply touch to program sample frequency, sample size, alarm settings, start mode, and units of measure. Use this invaluable tool in real-time mode or set it to start logging at a future time.

- ◆ Get accurate, reliable measurements with included NIST-traceable calibration
- ◆ Operation is simple right out of the box
- ◆ Resident operating software self-boots by pushing the on/off buttons—no installation necessary
- ◆ Quickly download data in .csv format to your computer via included USB cable
- ◆ Sensor plugs directly into the back of the tablet for local use, or position sensor remotely using the included 6-ft extension cable
- ◆ Link additional extension cables, sold separately, to extend the sensor up to 18 feet from the instrument
- ◆ Convenient wall-mount or desktop operation



**Precalibrated &  
Ready to Use!**

**novatech**  
INTERNATIONAL



Removable sensor allows local or remote measurements using extension cable

## Applications

- ◆ Food, pharmaceutical, and chemical processing and storage
- ◆ Controlled environments
- ◆ Refrigerators and freezers
- ◆ Laboratories
- ◆ Warehouses and storage facilities
- ◆ Museums
- ◆ Libraries
- ◆ Cleanrooms
- ◆ Greenhouses

\*Calibration certificate provided by InnoCal®, an ISO17025 accredited laboratory (A2LA certificate 1746.01) offering a broad range of NIST-traceable calibration services. For recalibration, call 866-466-6225 or e-mail [info@innocal.com](mailto:info@innocal.com). Their full complement of services can be viewed at [www.innocal.com](http://www.innocal.com).

## Includes

Tablet with built-in stand, temperature/RH sensor, 6-ft (1.8-m) sensor extension cable, USB cable, wall-mounting bracket, power supply, and NIST-traceable calibration with data supplied by InnoCal.

## Specifications

Parameters	Range	Resolution	Accuracy
Temperature	14 to 176°F (-10 to 80°C)	0.1°F (0.1°C)	±0.9°F (0.5°C)
Humidity	0 to 100% RH, noncondensing	0.1%	±2.0% at 25°C, 20% to 80% RH; ±2.5% for remaining

**Memory:** 8GB

**Sampling rate:** 1 second to 24 hours

**Display:** 6" x 3½" (15.2 x 8.9 cm) color LCD, with 1024 x 600 resolution

**Dimensions (W x H x D):** 7½" x 4¼" x ½"  
(19.3 x 10.8 x 1.6 cm)

**Power:** 110 VAC; 2500 mAH rechargeable battery backup



Catalog number	Description
<b>MW-20250-40</b>	Temperature/humidity touch-screen recorder
<b>MW-20250-47</b>	Additional extension cable for sensor, 6 ft (1.8 m)



USA

Cole-Parmer

IN CANADA

IN GERMANY

IN THE UNITED KINGDOM

IN INDIA

INTERNATIONAL CUSTOMERS

For Calibration,  
InnoCal

IN CHINA