



WT 1010M 1 CHANNEL MICRO SOLDERING KIT, 95 W, 120 V

ORDER NO: WT1010M

COMPACT. POWERFUL. VERSATILE.
BOOST YOUR PRODUCTIVITY

Discover the WT 1M Soldering Station, your ultimate productivity partner.

With extremely fast heat-up and recovery times, it handles all tasks effortlessly. No more juggling tools or compromising performance – just reliable versatility and unmatched value. Choose worry-free precision and unstoppable productivity. Choose Weller WT Soldering Stations.

+ KEY FEATURES

- > **1 CHANNEL MICRO SOLDERING KIT (95 W)**
to cover micro and standard soldering tasks including
WTMP MS Micro pencil with active (cartridge) tip technology
- > **RTM TIP FAMILY**
with 5 seconds heat-up time
- > **HIGH PRODUCTIVITY**
- > **INTUITIVE USE**
thanks to clear menu structure
- > **REDUCED FOOTPRINT**
thanks to stackability
- > **GRAPHICAL BACKLIT LC-DISPLAY**
- > **HIGH PERFORMANCE AND FUNCTIONALITY**
many connectable tools
- > **HOUSING COVER**
useable as storage
- > **OFF TIME, PROCESS WINDOW,**
Lock function, Offset
- > **STACKABLE UNITS**
useable as storage
- > **CONNECTABLE TO**
ZeroSmog Fume Extraction Units
- > **ESD-SAFE** 

#PowerfulTogether

SCOPE OF SUPPLY
WT1M Power Unit, 120V WTMP MS Soldering Iron, 12V RTM 013 S MS Micro Soldering Tip WSR 205 Safety Rest with Stop & Go Function

TECHNICAL DATA SOLDERING STATION WT 1010M
Dimensions L x W x H (mm) 150 x 130 x 101 Dimensions L x W x H (inch) 5.91 x 5.12 x 3.98
Fuse 120V (mA) T1
Weight approx. (kg) 1,9
Mains supply voltage (V/Hz) 120 / 50
Power consumption (W) 95
Safety class I, antistatic housing III, Soldering tool
Temperature range / Tool dependent °C 50 - 450 / 550
Temperature accuracy °C ± 9 / ± 17
Temperature stability °C ± 2
Subject to technical alterations and amendments.

TECHNICAL DATA SOLDERING IRON WTMP MS
Temperature range °C 100 - 450 Temperature range °F 150 - 950
Power consumption (W) 40W (55W)
Mains supply voltage (V/Hz) 12V / AC
Heat-up time (50°C to 350°C) (120°F to 660°F) 5 sec.
Safety rest WSR 205
Tip type series RTM MS
Supply unit WT 1M, WT 2M, WR 3M
Subject to technical alterations and amendments.