




## WT1012M 1 CHANNEL REWORK KIT, 95 W, 120 V ORDER NO: WT1012M

COMPACT. POWERFUL. VERSATILE.  
BOOST YOUR PRODUCTIVITY

### Discover the WT 1M Soldering Station, your ultimate productivity partner.

With extremely fast heat-up and recovery times, it handles all tasks effortlessly. No more juggling tools or compromising performance – just reliable versatility and unmatched value. Choose worry-free precision and unstoppable productivity. Choose Weller WT Soldering Stations.

## + KEY FEATURES

- > **1 CHANNEL REWORK KIT (95 W)**  
to cover micro and standard soldering and desoldering tasks including WTMT MS Micro tweezers with active (cartridge) tip technology
- > **RTW TIP FAMILY**  
5 seconds heat-up time
- > **HIGH PRODUCTIVITY**
- > **INTUITIVE USE**  
thanks to clear menu structure
- > **REDUCED FOOTPRINT**  
thanks to stackability
- > **GRAPHICAL BACKLIT LC-DISPLAY**
- > **HIGH PERFORMANCE AND FUNCTIONALITY**  
many connectable tools
- > **HOUSING COVER**  
useable as storage
- > **OFF TIME, PROCESS WINDOW,**  
Lock function, Offset Stackable units
- > **CONNECTABLE TO**  
ZeroSmog Fume Extraction Units
- > **STATION SET**  
to cover smallest to standard rework tasks
- > **MICRO DESOLDERING TOOLS**  
with active (cartridge) tips 5 seconds heat-up time
- > **STACKABLE UNITS**  
with active (cartridge) tips 5 seconds heat-up time
- > **ESD-SAFE** 

#PowerfulTogether

SCOPE OF SUPPLY
WT1M Power Unit, 120V WTMT MSTweezers, 80 W, 24V RTWMS 030 K Micro Tips (2 x 40 W) WSR 211 Safety Rest with Stop & Go Function

TECHNICAL DATA SOLDERING STATION WT 1M
<b>Dimensions L x W x H (mm)</b> 150 x 130 x 101 <b>Dimensions L x W x H (inch)</b> 5.91 x 5.12 x 3.98
<b>Fuse</b> 120V (mA) T1
<b>Weight approx. (kg)</b> 1,9
<b>Mains supply voltage (V/Hz)</b> 120 / 50 120 / 60 100 / 50/60
<b>Power consumption (W)</b> 95
<b>Safety class</b> I, antistatic housing III, Soldering tool
<b>Temperature range / Tool dependent</b> °C 50 - 450 / 550 °F 150-850 / 950
<b>Temperature accuracy (°C/°F)</b> ± 9 / ± 17
<b>Temperature stability (°C/°F)</b> ± 2 / ± 4
<b>Subject to technical alterations and amendments.</b>

TECHNICAL DATA WTMT MS MICRO TWEEZERS
<b>Temperature range</b> °C 100 - 450 <b>Temperature range</b> °F 200 - 850
<b>Power consumption</b> 80 W (2 x 40 W)
<b>Mains supply voltage (V/Hz)</b> 12V / AC
<b>Heat-up time (50°C to 350°C) (120°F to 660°F)</b> 5 sec.
<b>Safety rest</b> WSR 211
<b>Tip type series</b> RTWMS / RTWPS
<b>Supply unit</b> WT 1M, WT 2M, WR 3M
<b>Subject to technical alterations and amendments.</b>