



## WT2023M 2 CHANNEL REWORK KIT, 150 W, 120 V

ORDER NO: WT2023M

COMPACT. POWERFUL. VERSATILE.  
BOOST YOUR PRODUCTIVITY

### Discover the WT 2M Soldering Station, your ultimate productivity partner.

With extremely fast heat-up and recovery times, it handles all tasks effortlessly. No more juggling tools or compromising performance – just reliable versatility and unmatched value. Choose worry-free precision and unstoppable productivity. Choose Weller WT Soldering Stations.

### + KEY FEATURES

- > **2 CHANNEL REWORK KIT (150 W)**  
to cover micro and standard soldering and desoldering tasks including WTMP MS Micro pencil and WTMT MS Micro tweezers with active (cartridge) tip technology
- > **RTM AND RTW TIP FAMILY**  
5 seconds heat-up time
- > **HIGH PRODUCTIVITY**
- > **INTUITIVE USE**  
thanks to clear menu structure
- > **REDUCED FOOTPRINT**  
thanks to stackability
- > **GRAPHICAL BACKLIT LC-DISPLAY**
- > **HIGH PERFORMANCE AND FUNCTIONALITY**  
many connectable tools
- > **HOUSING COVER**  
useable as storage
- > **OFF TIME, PROCESS WINDOW,**  
Lock function, Offset Stackable units
- > **CONNECTABLE TO**  
ZeroSmog Fume Extraction Units
- > **STATION SET**  
to cover smallest to standard rework tasks
- > **MICRO DESOLDERING TOOLS**  
with active (cartridge) tips 5 seconds heat-up time
- > **STACKABLE UNITS**
- > **CONNECTABLE**  
to ZeroSmog Fume Extraction Units
- > **ESD-SAFE**



#PowerfulTogether

SCOPE OF SUPPLY
WT2M Power Unit, 120V WTMP MS Micro Soldering Iron, 40 W, 12V RTM 013 S MS Micro Soldering Tip WSR 205 Safety Rest with Stop & Go Function WTMT MS Micro/Nano Tweezers, 80 W, 12V RTWMS 030 K Micro Tips (2 x 40 W) WSR 11 Safety Rest with Stop & Go Function

TECHNICAL DATA SOLDERING STATION WT 2M
<b>Dimensions L x W x H (mm)</b> 150.0 x 130.0 x 101.0mm <b>Dimensions L x W x H (inch)</b> 5.91 x 5,43 x 3.98
<b>Fuse</b> T0,8
<b>Weight approx. (kg)</b> 1,9
<b>Mains supply voltage (V/Hz)</b> 120 / 50 120 / 60 100 / 50/60
<b>Power consumption (W)</b> 150 W
<b>Safety class</b> I, antistatic housing III, Soldering tool
<b>Temperature range / Tool dependent</b> 50 - 450 / 550 °C 150-850 / 950 °F
<b>Temperature accuracy</b> ± 9 °C / ± 17 °F
<b>Temperature stability</b> °C ± 2 / ± 4 °F
<b>Subject to technical alterations and amendments.</b>

TECHNICAL DATA	SOLDERING IRON WTMP MS	TWEETTER WTMT MS MS
<b>Temperature range</b> <b>Temperature range</b>	°C 100 - 450 °F 200 - 950	°C 100 - 450 °F 200 - 950
<b>Power consumption</b>	40 W (55 W)	80 W (2x40 W)
<b>Mains supply voltage (V/Hz)</b>	12V / AC	12V / AC
<b>Heat-up time (50°C to 350°C) (120°F to 660°F)</b>	5 sec.	5 sec.
<b>Safety rest</b>	WSR 205	WSR 211
<b>Tip type series</b>	RTM MS	RTWMS / RTWPS
<b>Supply unit</b>	WT 1M, WT 2M, WR 3M	WT 1M, WT 2M, WR 3M
<b>Subject to technical alterations and amendments.</b>		