



		<b>WINGTWIST™ WIRE CONNECTORS</b>		<b>MODELS WT51, WT41, WT52, WT54</b>																																										
<b>FEATURES/BENEFITS:</b>																																														
		<ul style="list-style-type: none"> <li>- CONTOURED WING DESIGN PROVIDES MAXIMUM TORQUE</li> <li>- EXPANDING, SQUARE-WIRE SPRING CREATES SECURE CONNECTIONS</li> <li>- WIDE, DEEP SKIRT OPENING ACCOMODATES A VARIETY OF WIRE COMBINATIONS</li> </ul>																																												
<b>ELECTRICAL:</b>			<b>APPLICATION TOOLS:</b>																																											
<b>VOLTAGE:</b> GENERAL: 600 V MAX SIGN/LUMINAIRES: 1000 V MAX			- Spin-Twist Wire Connector Socket																																											
<b>PHYSICAL:</b>			<b>STANDARDS &amp; SPECIFICATIONS:</b>																																											
HOUSING: <b>THERMOPLASTIC POLYESTER</b> INSERT: STEEL PLATING: ZINC TEMPERATURE: 105° C (221° F)			UL 486 C UL 94V-2 FLAME RATING CSA- C22.2 NO. 188 RoHS COMPLIANT																																											
<b>WIRE RANGE &amp; COMBINATIONS:</b>																																														
- Solid and/or stranded wire combinations unless stated otherwise - Consult website for other combinations not listed																																														
<b>WT51 (YELLOW)</b>		<b>WT41 (TAN)</b>		<b>WT52 (RED)</b>																																										
STRIP LENGTH: 3/8"		STRIP LENGTH: 1/2"		STRIP LENGTH: 1/2"																																										
<b>600V MAX:</b> 2 to 4 #18 1 #16 w/ 1 to 5 #18 2 to 4 #16 1 to 3 #14 1 to 3 #12 1 #10 1 #10 w/ 1 #12		<b>600V MAX:</b> 3 to 6 #22 2 to 6 #20, #18, or #16 1 to 5 #14 1 to 3 #12 4 #12 solid 1 to 3 #10		<b>600V MAX:</b> 2 to 3 #10 2 to 5 #12 2 to 6 #14 4 to 6 #14 6 #18																																										
<b>WT54 (BLUE)</b>																																														
STRIP LENGTH: 5/8"																																														
<b>600V MAX:</b> 5 to 6 #14 3 to 6 #12 2 to 5 #10 2 to 3 #8 1 to 2 #6																																														
<b>DIMENSIONS:</b>																																														
		<table border="1"> <thead> <tr> <th rowspan="2">MODEL</th> <th colspan="2">A</th> <th colspan="2">B</th> <th colspan="2">C</th> </tr> <tr> <th>INCHES</th> <th>mm</th> <th>INCHES</th> <th>mm</th> <th>INCHES</th> <th>mm</th> </tr> </thead> <tbody> <tr> <td>WT51</td> <td>1.02</td> <td>25.8</td> <td>0.52</td> <td>13.0</td> <td>0.73</td> <td>18.6</td> </tr> <tr> <td>WT41</td> <td>1.13</td> <td>28.7</td> <td>0.54</td> <td>13.8</td> <td>0.73</td> <td>18.5</td> </tr> <tr> <td>WT 52</td> <td>1.26</td> <td>32.0</td> <td>0.62</td> <td>16.0</td> <td>0.90</td> <td>23.0</td> </tr> <tr> <td>WT54</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>				MODEL	A		B		C		INCHES	mm	INCHES	mm	INCHES	mm	WT51	1.02	25.8	0.52	13.0	0.73	18.6	WT41	1.13	28.7	0.54	13.8	0.73	18.5	WT 52	1.26	32.0	0.62	16.0	0.90	23.0	WT54						
MODEL	A		B		C																																									
	INCHES	mm	INCHES	mm	INCHES	mm																																								
WT51	1.02	25.8	0.52	13.0	0.73	18.6																																								
WT41	1.13	28.7	0.54	13.8	0.73	18.5																																								
WT 52	1.26	32.0	0.62	16.0	0.90	23.0																																								
WT54																																														
<b>ORDERING INFO:</b>																																														
		<b>WT51 (YELLOW)</b>		<b>WT41 (TAN)</b>		<b>WT52 (RED)</b>		<b>WT54 (BLUE)</b>																																						
CATALOG NUMBERS		<b>WT51-1</b> Box of 100 <b>WT51-B</b> Bag of 500 <b>WT51-500JR</b> Jar of 500 <b>WT51-SK</b> Barrel of 25,000		<b>WT41-1</b> Box of 100 <b>WT41-B</b> Bag of 500 <b>WT41-500JR</b> Jar of 500 <b>WT41-SK</b> Barrel of 25,000		<b>WT52-1</b> Box of 100 <b>WT52-B</b> Bag of 500 <b>WT52-500JR</b> Jar of 500 <b>WT52-SK</b> Barrel of 25,000		<b>WT54-1</b> Box of 50 <b>WT54-B</b> Bag of 100																																						