TECHNICAL DATA | WOHLER VIS 400



Wohler VIS 400 Video Inspection System

TECHNICAL DATA

TFT display	Monitor	
Power supply 12 V NiMH rechargeable battery, 2.000 mAh Battery operating time 2 h (battery status in display) Distance measurement Digital meter counter in conjunction with the camera viper and cable reel Storage 4 GB SD card (2.5 h recording capacity) Interface Mini USB port Operating temperature 32104 °F Storage temperature -4122 °F Dimensions housing with v 2" Dimensions housing with pouch	TFT display	7" / 16:9 format
Battery operating time. 2 h (battery status in display) Distance measurement Digital meter counter in conjunction with the camera viper and cable reel Storage. 4 GB SD card (2.5 h recording capacity) Interface Mini USB port Operating temperature 32104 °F Storage temperature -4122 °F Dimensions housing without pouch with pouch	Video out	FBAS signal
Distance measurementDigital meter counter in conjunction with the camera viper and cable reel Storage	Power supply	12 V NiMH rechargeable battery, 2.000 mAh
with the camera viper and cable reel Storage	Battery operating time	2 h (battery status in display)
Storage	Distance measurement	Digital meter counter in conjunction
InterfaceMini USB port Operating temperature32104 °F Storage temperature4122 °F Dimensions housing without pouch		with the camera viper and cable reel
Operating temperature	Storage	4 GB SD card (2.5 h recording capacity)
Storage temperature -4122 °F Dimensions housing without pouch without pouch	Interface	Mini USB port
Dimensions housing without pouch	Operating temperature	32104 °F
without pouch	Storage temperature	4122 °F
Dimensions housing with pouch	Dimensions housing	
with pouch	without pouch	8" x 8" x 2"
WeightWithout pouch 3 lbs; with pouch 4 lbs	Dimensions housing	
	with pouch	9" x 9" x 3"
Connection, standStandard	Weight	Without pouch 3 lbs; with pouch 4 lbs
	Connection, stand	Standard