# WXR3 **Rework Station** www





- Used for soldering and desoldering of both large and small SMT components
- 2 internal pumps provide the sources for hot air, desoldering vacuum and a vacuum pick up tool for a completely self-contained rework system
- LCD display simultaneously monitors all parameters, connected tools and peripheral devices. Adjust parameter setting and other functions through menu.
- Compatible with all WX tools, accessories, and peripherals

### **TOOL COMPARISON BY SET**

Catalog & order no.	WXR3	WXR3001 SET*	WXR3002 SET*	WXR3003 SET*
Hot air pencil	N/A	WXHAP200 (200w / 24v)	WXHAP200 (200w / 24 v)	WXHAP200 (200w / 24v)
Desoldering iron	N/A	WXDP120 (120w / 24v)	WXDP120 (120w / 24 v)	WXDV120 (120w / 24v)
Soldering iron	N/A	WXP65 (65w / 24v)	WXP120 (120w / 24v)	WXP65 (65w / 24v)
List price	\$1,600.00	\$2,350.000	\$2,400.000	\$2,350.000

<sup>\*</sup>All sets include: the WXR Rework Station, hot air pencil with nozzles, desoldering iron and soldering iron with tips, WVP vacuum pickup pen with cups, desoldering tiplet, and WDH30, WDH70, WDH10 safety rests.



99 Washington Street Melrose, MA 02176 Phone 781-665-1400 Toll Free 1-800-517-8431





WXP65 (65w / 24v)
Order no.T0052921199



WXP120 (120w / 24v) Order no. T0052920199





WXDP120 (120w / 24v) Order no.T0051320199



WXDV120 (120w / 24v) Order no.T0051320499





WXHAP200 (200w / 24v) Order no.T0052711999



99 Washington Street Melrose, MA 02176 Phone 781-665-1400 Toll Free 1-800-517-8431

# WXR3 Rework Station 🖘



## All sets include:

- WXR rework unit
- Hot air pencil / nozzles
- Desoldering iron / tips
- Soldering iron / tips
- WVP vacuum pickup pen / vacuum cups
- Desoldering tiplet
- 3 safety rests

WXR3001 and WXR 3002 sets come with WDH30, WDH70, WDH10 safety rests. WXR3003 set comes with WDH40, for the WXDV120 desoldering iron.

#### **SPECIFICATIONS**

420w (600w)			
Temperature range Sold./Desold. 100°C – 450°C (200°F – 850°F) Hot air pencil 100°C – 550°C (200°F – 999°F)			
± 54°F	(± 9°C) (± 30°C) (± 9°C)		
± 4°F	(± 2°C)		
Mains supply 120 VAC / 60Hz			
USB interface and RS 232 interface			
Pump Intermittant mode: max. hot air 15 l/min Max. vacuum 0.5 bar, max. delivery rate 1.7 l/mir			
	C (200°F C (200°F ± 17°F ± 54°F ± 17°F ± 4°F		

	lied	

ESD safe

ups		
•	WXP65	XTNA
	WXP120	XTB
	WXDP120	XDS3, XDS5
	WXDV120	XDS3, XDS5
	WXHAP200	R04, R06
		yes

#### ORDER INFORMATION

Foreign trade code

Package length	10.75 in	
Package width	9.25 in	
Package height	4.02 in	
Package gross weigh	6.7 kg	
UPC		
	WXR3	037103288653
	WXR3001	037103288684
	WXR3002	037103288677
	WXR3003	037103288660
Country of origin		Germany



(Kits) 8515110000 (WXR3) 8515190000

