



### Product information



### Zero Smog 6V mobile fume extraction

Code No. : **T0053667699**

for adhesive fumes volume extraction

Mobile fume extraction unit 230 V/50 Hz, for volume extraction with built in turbine. For upto 6 workplaces. One connection included, further connections must be ordered separately

### \*\*\*Approved technology in new design\*\*\*

Weller Tools announces design changes for all fume extraction units of the new product line WellerFT

According to the official announcement of the consolidation of Weller Zero-Smog and Filtronic to the new brand WellerFT filter system, all products will be produced in a new unique color.



(change date February 2014)

### Technical Data



This station is ESD safe

**Dimensions L x B xH:** 450 x 450 x 650 mm

**Weight:** 40 kg

**Voltage:** 230 V/50 Hz (

**Sound level in 1m:** 51 dB(A)

<b>Electrical power:</b>	460 VA
<b>Max. vacuum:</b>	2800Pa
<b>Max. capacity:</b>	615 m <sup>3</sup> /h
<b>Fine dust filter:</b>	Fine dust filter F 7
<b>Filter:</b>	Filter for adhesive fumes (wide band gas filter 50% active carbon, 50% Puratex)
<b>RS232 port</b>	All system functions can be operated and remotely monitored via the RS232 port
<b>USBport</b>	<p>The USB port can be used to load firmware updates, run efficiency tests and log data.</p> <p>Do not leave the USB medium inserted for longer than 2 minutes. After this time expires, the USB module will switch off automatically.</p>

